

GENERAL TIRE  TM

GENERALTIRE.COM



PASSENGER & LIGHT TRUCK

PRODUCT DATA GUIDE

2023 | 1ST EDITION



DELIVERS

Making the most of every moment can be demanding. Which is why, at General Tire, we think you should demand more from your tires. For more than a century, we've made great all around tires that always deliver the right combination of performance, durability, style and value. All so we can deliver the tire experience you need for whatever life demands. Taking the kids to school and back? We deliver reliability. Turning heads on the daily commute? We deliver distinction. Tackling your favorite off road trail? We deliver more traction. For all kinds of reasons, for all kinds of seasons, General Tire delivers. Because that's what we demand of ourselves. And that's what we think you deserve.

General Tire does not recommend replacing one tire at a time on a vehicle. Fitting a vehicle with an improper mix of tire sizes, constructions, and speed ratings can be dangerous. Consult the vehicle owner's manual to determine proper mixing, matching, or when replacing tires with different sizes, constructions, and speed ratings. If all of the ground tires are not replaced at one time, then at a minimum, General Tire recommends replacing all tires on the same axle at one time (see the vehicle owner's manual for 4x4 vehicles for whether there are additional recommendations). This is especially recommended for tires that are listed in this product guide with alternate article numbers. Tires that are identified with alternate article numbers are nearly identical to the tires that they are replacing, but may have slight differences. One difference can be the tread design or pattern which can make the alternate tires incompatible for mixing on the same axle as a different tire.

CONTENTS

PRODUCT OVERVIEW

PRODUCT LINE OVERVIEW	4
TECHNOLOGY OVERVIEW	6
FLOTATION SIZE EQUIVALENCY CHART	8
QUICK REFERENCE GUIDE	10

REPLACEMENT TIRE PRODUCTS

ULTRA-HIGH PERFORMANCE

G-MAX™ RS SUMMER PASSENGER & CROSSOVER	20
G-MAX™ AS ⁰⁵ ALL-SEASON PASSENGER & CROSSOVER	24
Grabber™ UHP ALL-SEASON CROSSOVER, LIGHT TRUCK & SUV	28

TOURING

AltiMAX™ RT ⁴⁵ ALL-SEASON PASSENGER & CROSSOVER	32
AltiMAX™ ³⁶⁵ AW ALL-WEATHER PASSENGER & CROSSOVER	36
Grabber™ HTS ⁶⁰ ALL-SEASON CROSSOVER, LIGHT TRUCK & SUV	40

ALL-TERRAIN

Grabber™ APT ALL-SEASON CROSSOVER, LIGHT TRUCK & SUV	46
Grabber™ A/T ^X ALL-SEASON LIGHT TRUCK & SUV	48
Grabber™ X ³ ALL-SEASON LIGHT TRUCK & SUV	52

WINTER

AltiMAX™ Arctic ¹² TOURING PASSENGER & CROSSOVER	58
Grabber™ Arctic ALL-TERRAIN LIGHT TRUCK & SUV	62
Grabber™ Arctic LT ALL-TERRAIN LIGHT TRUCK & SUV	64

GOVERNMENT & FLEET / COMMERCIAL

Grabber™ HD ALL-SEASON LIGHT TRUCK & SUV	68
Grabber™ HD Van ALL-SEASON CARGO VAN	70
G-MAX™ Justice ALL-SEASON HIGH-SPEED PURSUIT	72
G-MAX™ Justice AW ALL-WEATHER HIGH-SPEED PURSUIT	74

ORIGINAL EQUIPMENT PRODUCTS

OE PRODUCT LINE OVERVIEW	76
OE REFERENCE GUIDE PRODUCT LINE	77
OE REFERENCE GUIDE VEHICLE FITMENT	78

WARRANTY INFORMATION

LIMITED WARRANTY & ADJUSTMENT POLICY	80
TREADWEAR CONVERSION TABLE	81
LEGAL OBLIGATION	82

REPLACEMENT PRODUCT LINE OVERVIEW



AltiMAX™ 365 AW

A versatile, all-weather touring tire for passenger cars and crossovers, the AltiMAX™ 365 AW ranges in size from 15-20" rim diameter.



AltiMAX™ Arctic¹²

A studdable winter tire for passenger cars and crossovers, the AltiMAX™ Arctic¹² ranges in size from 14-19" rim diameter.



AltiMAX™ RT⁴⁵

A long-lasting, all-season touring tire for passenger cars and crossovers, the AltiMAX™ RT⁴⁵ ranges in size from 14-20" rim diameter.



G-MAX™ AS⁰⁵

A dynamic, all-season ultra-high performance tire for passenger cars and crossovers, the G-MAX™ AS⁰⁵ ranges in size from 16-22" rim diameter.



G-MAX™ Justice

A durable, all-season high-speed pursuit tire for government and fleet vehicles, the G-MAX™ Justice ranges in size from 16-20" rim diameter.



G-MAX™ Justice AW

A versatile, all-weather high-speed pursuit tire for government and fleet vehicles, the G-MAX™ Justice AW ranges in size from 17-20" rim diameter.



G-MAX™ RS

An excellent, summer ultra-high performance tire for passenger cars and crossovers, the G-MAX™ RS ranges in size from 16-20" rim diameter.



Grabber™ A/T^x

An aggressive, all-season all-terrain tire for light trucks and SUVs, the Grabber™ A/T^x ranges in size from 14-20" rim diameter.



Grabber™ APT

A durable, all-season all-terrain tire for crossovers, light trucks and SUVs, the Grabber™ APT ranges in size from 16-22" rim diameter.



Grabber™ Arctic

A studdable winter tire for light trucks and SUVs, the Grabber™ Arctic ranges in size from 16-20" rim diameter.



Grabber™ Arctic LT

A studdable winter tire for light trucks and SUVs, the Grabber™ Arctic LT ranges in size from 16-20" rim diameter.



Grabber™ HD

A durable, all-season commercial tire for light trucks and SUVs, the Grabber™ HD ranges in size from 16-18" rim diameter.



Grabber™ HD Van

A durable, all-season commercial tire for cargo vans, the Grabber™ HD Van ranges in size from 15-16" rim diameter.



Grabber™ HTS⁶⁰

A long-lasting, all-season touring tire for crossovers, light trucks and SUVs, the Grabber™ HTS⁶⁰ ranges in size from 15-22" rim diameter.



Grabber™ UHP

A long-lasting, all-season ultra-high performance tire for crossovers, light trucks and SUVs, the Grabber™ UHP ranges in size from 16-24" rim diameter.



Grabber™ X³

An extreme, all-season mud-terrain tire for light trucks and SUVs, the Grabber™ X³ ranges in size from 15-22" rim diameter.

REPLACEMENT PRODUCT LINE OVERVIEW CHART

PRODUCT LINES	TREAD PATTERN	RIM SIZE	SPEED RATING	UTQG (WEAR, TRACTION, TEMPERATURE)		MILEAGE WARRANTY*	CUSTOMER SATISFACTION TRIAL	PAGE #
AltiMAX™ 365 AW	Symmetric	15"-20"	H, V	640 A A (H)	540 A A (V)	60,000 Miles	45 Days	36
AltiMAX™ Arctic ¹²	Directional	14"-19"	T	--		--	45 Days	58
AltiMAX™ RT ⁴⁵	Symmetric	14"-20"	T, H, V	600 A B (T) 600 A A (H, V) 700 A B (T) 700 A A (H, V)		75,000 Miles (T & H) 65,000 Miles (V)	45 Days	32
G-MAX™ AS ⁰⁵	Asymmetric	16"-22"	W	500 AA A (Load ≤ 103)	500 A A (Load ≥ 104)	50,000 Miles	45 Days	24
G-MAX™ Justice	Asymmetric	16"-20"	V, W	440 AA A		--	--	72
G-MAX™ Justice AW	Symmetric	17"-20"	V	540 A A		--	--	74
G-MAX™ RS	Directional	16"-20"	W, Y	360 AA A		--	45 Days	20
Grabber™ A/T ^X	Symmetric	14"-20"	Q, R, S, T	640 A B (Excludes LT Metric)		60,000 Miles (P Metric) 50,000 Miles (LT Metric)	45 Days	48
Grabber™ APT	Symmetric	16"-22"	R, S, T, H	520 A B (Excludes LT Metric)		60,000 Miles	45 Days	46
Grabber™ Arctic	Directional	16"-20"	T	--		--	45 Days	62
Grabber™ Arctic LT	Symmetric	16"-20"	R	--		--	45 Days	64
Grabber™ HD	Symmetric	16"-18"	R, S	--		--	45 Days	68
Grabber™ HD Van	Symmetric	15"-16"	R, T	--		--	45 Days	70
Grabber™ HTS ⁶⁰	Symmetric	15"-22"	S, T H S, R	680 A B (P Metric) 660 A A (P Metric) -- (LT Metric)		65,000 Miles (P Metric) 50,000 Miles (P Metric) 50,000 Miles (LT Metric)	45 Days	40
Grabber™ UHP	Directional	16"-24"	H, V, W	320 A A (Series ≤ 50)	360 A A (Series ≥ 55)	--	45 Days	28
Grabber™ X ³	Symmetric	15"-22"	Q	--		--	45 Days	52

*Rear axle split fitments will be 50% of standard tread wearout coverage **Select Sizes only.





TIRE TECHNOLOGY & FEATURES



ex. Grabber A/T*



ex. G-MAX AS⁰⁵

1 3-Peak Mountain Snowflake	2 Duragen™ Technology	3 Replacement Tire Monitor®	4 Visual Alignment Indicators®
 <p>Meets the severe snow service requirements of the U.S. Tire Manufacturer's Association (USTMA) and the Tire and Rubber Association of Canada (TRAC).</p> <p>Available On: AltiMAX™ 365 AW AltiMAX™ Arctic¹² G-MAX™ Justice AW Grabber™ A/T^x Grabber™ APT Grabber™ Arctic Grabber™ Arctic LT</p>	 <ul style="list-style-type: none"> - Enhances strength and durability - Delivers cut-and-chip resistance - Extends tread life <p>Available On: Grabber™ A/T^x Grabber™ APT Grabber™ Arctic Grabber™ Arctic LT Grabber™ HD Grabber™ HD Van Grabber™ HTS⁶⁰ Grabber™ X³</p>	 <p>Letters in the tread wear off to read "REPLACE TIRE" when the tire wears to 2/32 of tread depth, indicating a tire change is needed.</p> <p>Available On: AltiMAX™ RT⁴⁵ G-MAX™ AS⁰⁵ G-MAX™ RS</p>	 <p>Indicators in both sides of the tread wear off evenly, ensuring the driver of proper alignment, or wear off unevenly, alerting the driver to check the wheel alignment.</p> <p>Available On: AltiMAX™ 365 AW AltiMAX™ RT⁴⁵ G-MAX™ AS⁰⁵</p>



AltimaX™ 365 AW
VAI



AltimaX™ Arctic¹²



AltimaX™ RT⁴⁵
RTM VAI



G-MAX™ AS⁰⁵
RTM VAI



G-MAX™ Justice



G-MAX™ Justice AW



G-MAX™ RS
RTM



Grabber™ A/T^X
Duragen



Grabber™ APT
Duragen



Grabber™ Arctic
Duragen



Grabber™ Arctic LT
Duragen



Grabber™ HD
Duragen



Grabber™ HD Van
Duragen



Grabber™ HTS⁶⁰
Duragen



Grabber™ UHP



Grabber™ X³
Duragen

Available Features Legend:

▲ 3-Peak Mountain Snowflake Duragen® Technology RTM Replacement Tire Monitor® VAI Visual Alignment Indicators®

LT METRIC TO FLOTATION SIZE EQUIVALENT

RIM SIZE	LT METRIC SIZE		RIM SIZE	FLOTATION SIZE EQUIVALENT
17	LT285/70R17	➤	17	33X11.00R17
	LT295/70R17			33X11.50R17
	LT315/70R17			35X12.50R17
18	LT275/65R18	➤	18	32X11.00R18
	LT275/70R18			33X11.00R18
	LT285/60R18			32X11.00R18
	LT285/65R18			33X11.00R18
	LT285/70R18			34X11.00R18
	LT285/75R18			35X11.00R18
	LT295/70R18			34x11.50R18
	LT305/65R18			34X12.00R18
	LT315/70R18			36X12.50R18
20	LT275/55R20	➤	20	32X11.00R20
	LT275/65R20			34X11.00R20
	LT285/55R20			32X11.00R20
	LT285/60R20			34X11.00R20
	LT295/55R20			33X11.50R20
	LT295/60R20			34X11.50R20
	LT295/65R20			35X11.50R20
	LT305/55R20			33X12.00R20
	LT315/60R20			35X12.50R20
	LT325/60R20			35X13.00R20
22	LT285/50R22	➤	22	33X11.00R22
	LT325/50R22			35X13.00R22

*Flotation sizes are estimates only and should not be used as a substitute for the recommendation of a certified tire installer. Load ratings and inflation requirements may vary between LT Metric and Flotation sizes. Products should only be used in applications approved by the manufacturer. Please consult your tire installer for a recommendation of the products suitable for your application.

GENERAL TIRE ™

DELIVERS

QUICK REFERENCE GUIDE

QUICK REFERENCE GUIDE

RIM DIA (IN)	TIRE SIZE	REPLACEMENT TIRES														ORIGINAL EQUIPMENT TIRES				
		G-MAX™ RS	GMAX™ AS05	Grabber™ UHP	AlliMAX™ RT45	AlliMAX™ 365 AW	Grabber™ HTS60	Grabber™ APT	Grabber™ A/TX	Grabber™ X3	AlliMAX™ Arctic12	Grabber™ Arctic	Grabber™ Arctic LT	Grabber™ HD	Grabber™ HD Van	G-MAX™ Justice	G-MAX™ Justice AW	Ameritrac™	Ameritrac™ TR	Grabber™ HTS
14	27 X 8.50 R 14 LT								●											
	185/60 R 14				●															
	195/60 R 14				●															
	175/65 R 14				●						●									
	185/65 R 14				●						●									
	175/70 R 14				●						●									
	185/70 R 14				●						●									
	195/70 R 14				●															
	205/70 R 14				●															
	215/70 R 14				●															
225/70 R 14				●																
15	30 X 9.50 R 15 LT								●											
	31 X 10.50 R 15 LT						●		●	●										
	33 X 10.50 R 15 LT									●										
	33 X 12.50 R 15 LT									●	●									
	35 X 12.50 R 15 LT									●	●									
	185/55 R 15				●	●														
	195/55 R 15				●															
	185/60 R 15				●	●					●									
	185/60 R 15 C														●					
	195/60 R 15				●	●					●									
	205/60 R 15				●															
	215/60 R 15				●															
	225/60 R 15				●															
	175/65 R 15				●	●					●									
	185/65 R 15				●	●					●									
	195/65 R 15				●	●					●									
	205/65 R 15				●						●									
	215/65 R 15				●															
	195/70 R 15 C														●					
	205/70 R 15				●						●									
	215/70 R 15				●						●									
	225/70 R 15				●						●									●
	235/70 R 15				●															
	255/70 R 15						●				●									
	265/70 R 15										●									
	205/75 R 15										●									
	215/75 R 15										●									
235/75 R 15										●									●	
265/75 R 15						●														
LT235/75 R 15										●										
16	245/75 R 16																			●
	205/45 ZR 16		●																	
	195/50 R 16				●															

**QUICK
REFERENCE
GUIDE**

RIM DIA (IN)	TIRE SIZE	REPLACEMENT TIRES													ORIGINAL EQUIPMENT TIRES					
		G-MAX™ RS	GMAX™ AS05	Grabber™ UHP	AltMAX™ RT45	AltMAX™ 365 AW	Grabber™ HTS60	Grabber™ APT	Grabber™ A/TX	Grabber™ X3	AltMAX™ Arctic12	Grabber™ Arctic	Grabber™ Arctic LT	Grabber™ HD	Grabber™ HD Van	G-MAX™ Justice	G-MAX™ Justice AW	Ameritrac™	Ameritrac™ TR	Grabber™ HTS
16	195/50 ZR 16		●																	
	205/50 R 16				●															
	205/50 ZR 16		●																	
	225/50 ZR 16	●	●																	
	245/50 ZR 16	●																		
	185/55 R 16				●															
	195/55 R 16				●															
	205/55 R 16				●	●					●									
	205/55 ZR 16	●	●																	
	215/55 R 16				●	●					●									
	215/55 ZR 16		●																	
	225/55 R 16				●						●									
	225/55 ZR 16		●																	
	185/60 R 16				●															
	205/60 R 16				●	●					●									
	215/60 R 16				●	●					●									
	225/60 R 16				●	●					●						●			
	235/60 R 16				●						●									
	205/65 R 16				●	●					●									
	215/65 R 16				●	●				●	●									
	225/65 R 16				●	●					●									
	235/65 R 16				●															
	235/65 R 16 C								●							●				
	255/65 R 16			●			●													
	205/70 R 16				●															
	215/70 R 16				●	●	●		●		●									
	225/70 R 16				●		●				●									
	235/70 R 16						●	●	●		●									
	245/70 R 16						●													
	255/70 R 16						●	●	●											
	265/70 R 16						●	●	●		●									
	195/75 R 16 C															●				
	225/75 R 16						●		●											
	225/75 R 16 C													●						
	235/75 R 16						●													
	245/75 R 16						●	●			●									
265/75 R 16						●	●													
LT305/70 R 16								●												
LT225/75 R 16								●				●	●						●	
LT245/75 R 16						●	●	●				●	●							
LT265/75 R 16						●	●	●	●			●	●							
LT285/75 R 16								●	●											
LT315/75 R 16								●	●											
LT215/85 R 16								●					●							

QUICK REFERENCE GUIDE

RIM DIA (IN)	TIRE SIZE	REPLACEMENT TIRES														ORIGINAL EQUIPMENT TIRES				
		G-MAX™ RS	GMAX™ AS05	Grabber™ UHP	AlliMAX™ RT45	AlliMAX™ 365 AW	Grabber™ HTS60	Grabber™ APT	Grabber™ A/TX	Grabber™ X3	AlliMAX™ Arctic12	Grabber™ Arctic	Grabber™ Arctic LT	Grabber™ HD	Grabber™ HD Van	G-MAX™ Justice	G-MAX™ Justice AW	Ameritrac™	Ameritrac™ TR	Grabber™ HTS
16	LT235/85 R 16						●	●	●					●						
17	33 X 12.50 R 17 LT									●										
	35 X 12.50 R 17 LT								●	●										
	37 X 12.50 R 17 LT								●	●										
	205/40 ZR 17		●																	
	245/40 ZR 17	●	●																	
	255/40 ZR 17	●																		
	275/40 ZR 17	●	●																	
	205/45 R 17				●															
	205/45 ZR 17		●																	
	215/45 R 17				●	●					●									
	215/45 ZR 17	●	●																	
	225/45 R 17				●	●					●									
	225/45 ZR 17	●	●																	
	235/45 R 17				●	●					●									
	235/45 ZR 17	●	●																	
	245/45 R 17				●															
	245/45 ZR 17	●	●																	
	205/50 R 17				●	●					●									
	205/50 ZR 17	●	●																	
	215/50 R 17				●	●					●									
	215/50 ZR 17	●	●																	
	225/50 R 17				●	●					●									
	225/50 ZR 17	●	●																	
	235/50 R 17				●															
	235/50 ZR 17		●																	
	245/50 ZR 17		●																	
	215/55 R 17				●	●					●									
	215/55 ZR 17		●																	
	225/55 R 17				●	●					●									
	225/55 ZR 17		●																	
	235/55 R 17				●	●					●									
	235/55 ZR 17		●														●		●	
275/55 R 17			●																	
215/60 R 17				●	●					●										
225/60 R 17				●	●					●										
235/60 R 17				●	●					●										
255/60 R 17			●																	
265/60 R 17																●		●		
275/60 R 17						●														
215/65 R 17				●	●					●										
225/65 R 17				●	●					●										
235/65 R 17				●	●	●				●										
245/65 R 17						●	●				●									

**QUICK
REFERENCE
GUIDE**

RIM DIA (IN)	TIRE SIZE	REPLACEMENT TIRES														ORIGINAL EQUIPMENT TIRES				
		G-MAX™ RS	GMAX™ AS05	Grabber™ UHP	AltMAX™ RT45	AltMAX™ 365 AW	Grabber™ HTS60	Grabber™ APT	Grabber™ A/TX	Grabber™ X3	AltMAX™ Arctic12	Grabber™ Arctic	Grabber™ Arctic LT	Grabber™ HD	Grabber™ HD Van	G-MAX™ Justice	G-MAX™ Justice AW	Ameritrac™	Ameritrac™ TR	Grabber™ HTS
17	255/65 R 17						●	●												
	265/65 R 17						●	●	●			●								
	235/70 R 17						●													
	245/70 R 17						●	●	●			●								
	255/70 R 17							●	●											●
	265/70 R 17						●	●	●			●								
	P245/70 R 17																			●
	P285/70 R 17							●												
	235/75 R 17							●												
	255/75 R 17							●												
	LT245/70 R 17						●	●	●			●	●							
	LT265/70 R 17						●	●	●	●		●	●							
	LT275/70 R 17								●											
	LT285/70 R 17								●	●										
	LT295/70 R 17									●										
	LT315/70 R 17								●	●										
	LT245/75 R 17						●	●	●			●	●							●
	LT255/75 R 17									●										
	LT235/80 R 17						●	●	●				●					●	●	
18	33 X 12.50 R 18 LT								●											
	35 X 12.50 R 18 LT								●	●										
	37 X 12.50 R 18 LT								●											
	285/40 ZR 18	●																		
	275/70 R 18								●											
	295/30 ZR 18	●																		
	245/35 ZR 18	●																		
	255/35 ZR 18	●	●																	
	265/35 ZR 18	●	●																	
	275/35 ZR 18	●																		
	285/35 ZR 18	●																		
	215/40 ZR 18	●	●																	
	225/40 R 18				●	●														
	225/40 ZR 18	●	●																	
	235/40 ZR 18	●	●																	
	245/40 R 18				●	●														
	245/40 ZR 18	●	●																	
	255/40 ZR 18	●	●																	
	275/40 ZR 18	●	●																	
	215/45 ZR 18		●																	
	225/45 R 18				●	●					●									
225/45 ZR 18	●	●																		
235/45 R 18				●	●					●										
235/45 ZR 18		●																		
245/45 R 18				●	●															

QUICK REFERENCE GUIDE

RIM DIA (IN)	TIRE SIZE	REPLACEMENT TIRES														ORIGINAL EQUIPMENT TIRES				
		G-MAX™ RS	GMAX™ AS95	Grabber™ UHP	AltMAX™ RT45	AltMAX™ 365 AW	Grabber™ HTS60	Grabber™ APT	Grabber™ A/TX	Grabber™ X3	AltMAX™ Arctic12	Grabber™ Arctic	Grabber™ Arctic LT	Grabber™ HD	Grabber™ HD Van	G-MAX™ Justice	G-MAX™ Justice AW	Ameritrac™	Ameritrac™ TR	Grabber™ HTS
18	245/45 ZR 18	●	●																	
	255/45 ZR 18	●	●																	
	225/50 R 18				●	●					●									
	225/50 ZR 18		●																	
	235/50 R 18				●	●														●
	235/50 ZR 18	●	●														●			
	245/50 R 18				●															
	215/55 R 18				●															
	225/55 R 18				●	●					●									
	235/55 R 18				●	●					●									
	245/55 R 18				●	●											●		●	
	245/55 ZR 18		●																	
	255/55 R 18			●		●	●					●								
	225/60 R 18				●	●					●									●
	225/60 ZR 18																●			
	235/60 R 18				●	●	●				●									
	245/60 R 18					●	●					●								
	255/60 R 18																●		●	
	265/60 R 18						●	●				●								
	235/65 R 18				●	●	●													
	255/65 R 18						●					●								
	265/65 R 18						●	●				●								
	275/65 R 18						●	●	●			●								
	255/70 R 18						●	●												
	265/70 R 18						●	●	●										●	
	275/70 R 18								●											
	P275/70 R 18							●												
	LT265/60 R 18										●									
	LT285/60 R 18										●									
	LT275/65 R 18						●	●	●	●			●	●						
	LT285/65 R 18								●											
	LT265/70 R 18							●	●	●			●	●						
LT275/70 R 18						●	●	●	●			●	●							
LT295/70 R 18									●											
P 275/70 R 18							●													
LT 265/70 R 18							●													
19	235/55 ZR 19		●																	
	295/30 ZR 19	●																		
	305/30 ZR 19	●																		
	235/35 ZR 19	●																		
	245/35 ZR 19	●	●																	
	255/35 ZR 19	●	●																	
	265/35 ZR 19	●																		
275/35 ZR 19	●	●																		

**QUICK
REFERENCE
GUIDE**

RIM DIA (IN)	TIRE SIZE	REPLACEMENT TIRES														ORIGINAL EQUIPMENT TIRES				
		G-MAX™ RS	GMAX™ AS05	Grabber™ UHP	AltMAX™ RT45	AltMAX™ 365 AW	Grabber™ HTS60	Grabber™ APT	Grabber™ A/TX	Grabber™ X3	AltMAX™ Arctic12	Grabber™ Arctic	Grabber™ Arctic LT	Grabber™ HD	Grabber™ HD Van	G-MAX™ Justice	G-MAX™ Justice AW	Ameritrac™	Ameritrac™ TR	Grabber™ HTS
19	285/35 ZR 19	●	●																	
	225/40 ZR 19	●	●																	
	235/40 R 19				●															
	235/40 ZR 19		●																	
	245/40 R 19				●															
	245/40 ZR 19	●	●																	
	255/40 ZR 19	●	●																	
	275/40 ZR 19		●																	
	225/45 ZR 19	●	●																	
	235/45 R 19				●															
	245/45 R 19				●	●														
	245/45 ZR 19	●	●																	
	255/45 R 19				●															
	235/50 R 19				●															
	245/50 ZR 19		●																	
	255/50 R 19					●	●													
	255/50 ZR 19		●																	
	225/55 R 19				●	●					●									
	235/55 R 19				●	●	●													
	245/55 R 19				●	●	●													
255/55 R 19			●																	
255/60 R 19						●														
20	33 X 12.50 R 20 LT								●	●										
	35 X 12.50 R 20 LT								●	●										
	37 X 13.50 R 20 LT								●	●										
	305/35 ZR 20		●																	
	245/35 ZR 20		●																	
	255/35 ZR 20		●																	
	275/35 ZR 20	●	●																	
	285/35 ZR 20	●	●																	
	305/35 ZR 20	●																		
	245/40 R 20				●															
	245/40 ZR 20	●	●																	
	275/40 ZR 20	●	●																	
	245/45 R 20				●															
	245/45 ZR 20	●	●																	
	255/45 ZR 20		●																	
	295/45 R 20			●																
	245/50 R 20				●	●	●													
	255/50 R 20						●													
	265/50 R 20						●													
	295/50 R 20			●																
305/50 R 20									●											
235/55 R 20				●	●	●														

QUICK REFERENCE GUIDE

RIM DIA (IN)	TIRE SIZE	REPLACEMENT TIRES														ORIGINAL EQUIPMENT TIRES				
		G-MAX™ RS	GMAX™ AS05	Grabber™ UHP	AltMAX™ RT45	AltMAX™ 365 AW	Grabber™ HTS60	Grabber™ APT	Grabber™ A/TX	Grabber™ X3	AltMAX™ Arctic12	Grabber™ Arctic	Grabber™ Arctic LT	Grabber™ HD	Grabber™ HD Van	G-MAX™ Justice	G-MAX™ Justice AW	Ameritrac™	Ameritrac™ TR	Grabber™ HTS
20	255/55 R 20						●													
	275/55 R 20			●			●	●	●			●				●	●			
	245/60 R 20						●													
	275/60 R 20						●	●				●								
	LT275/55 R 20								●											
	LT285/55 R 20								●											
	LT295/55 R 20									●										
	LT305/55 R 20								●	●										
	LT265/60 R 20								●											●
	LT275/60 R 20								●											
	LT285/60 R 20								●											
	LT325/60 R 20								●											
	LT275/65 R 20						●		●	●			●							
	LT295/65 R 20									●										
LT 275/65 R 20							●													
22	37 X 13.50 R 22 LT									●										
	265/40 ZR 22		●																	
	305/40 R 22			●																
	285/45 R 22						●	●												
	305/45 R 22			●					●											
	275/50 R 22						●													
23	305/40 R 23			●																
24	305/35 R 24			●																

GENERAL TIRE  TM

DELIVERS

GENERAL TIRE ™

DELIVERS

for handling your everyday.

Our **ultra-high performance** products deliver superior handling in a variety of weather conditions with long-lasting treadwear.



G-MAX™ RS



G-MAX™ AS05



Grabber™ UHP





PASSENGER & CROSSOVER | SUMMER | ULTRA-HIGH PERFORMANCE

G-MAX™ RS

Rim Diameter



16" - 20"

Aspect Ratio



30 - 55

Tread Pattern



Directional

TREADWEAR	TRACTION	TEMPERATURE	SPEED
360	AA	A	W & Y

Benefits

- Best-in-class dry and wet handling*
- Best-in-class wet braking*
- Best-in-class treadwear*
- Preferred tire of Petty's Garage



Replacement Tire Monitor

Letters in the tread wear off to read "REPLACE TIRE" when the tire wears to 2/32 of tread depth, indicating a tire change is needed.

Sample Vehicle Fitments Include:

- Audi: A4, A6 & TT
 - BMW: 1-5 Series
 - Chevrolet Camaro
 - Dodge: Challenger & Charger
 - Ford Mustang
 - Mazda Miata
 - Mercedes-Benz: C & E-Class
 - Mini Cooper
 - Nissan 370Z
-
- OEM Vehicle Fitment for Saleen Mustang



CUSTOMER SATISFACTION TRIAL

Or the first 2/32^{nds} of tread. See warranty manual for complete details.

*Based on internal test results compared to Firestone Firehawk Indy 500, BF Goodrich g-Force Sport Comp2 and HankookVentus V12 evo2 in the size 245/40ZR18. On road results may vary.

G-MAX™ RS | Product Data

PASSENGER & CROSSOVER | SUMMER | ULTRA-HIGH PERFORMANCE

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ^{nds})	REVS PER MILE
16	50	225/50 ZR 16	92 W	SL	BSW	15492580000	Yes	24.9	21.5	51.0	9.2 (7.0)	(6.0 - 8.0)	1389	10	836
	50	245/50 ZR 16	97 W	SL	BSW	15492600000	Yes	25.6	24.5	51.0	10.0 (7.5)	(7.0 - 8.5)	1609	10	810
	55	205/55 ZR 16	91 W	SL	BSW	15492560000	Yes	24.9	21.2	51.0	8.4 (6.5)	(5.5 - 7.5)	1356	10	835
17	40	245/40 ZR 17	91 W	SL	BSW	15492690000	Yes	24.7	22.9	51.0	9.8 (8.5)	(8.0 - 9.5)	1356	10	840
	40	255/40 ZR 17	94 W	SL	BSW	15492710000	Yes	25.0	24.1	51.0	10.2 (9.0)	(8.5 - 10.0)	1477	10	830
	40	275/40 ZR 17	98 W	SL	BSW	15492720000	Yes	25.7	24.1	51.0	10.9 (9.5)	(9.0 - 11.0)	1653	10	810
	45	215/45 ZR 17	91 W	XL	BSW	15492630000	Yes	24.6	20.3	51.0	8.4 (7.0)	(7.0 - 8.0)	1356	10	844
	45	225/45 ZR 17	91 W	SL	BSW	15492650000	Yes	25.0	20.4	51.0	8.9 (7.5)	(7.0 - 8.5)	1356	10	832
	45	235/45 ZR 17	94 W	SL	BSW	15492670000	Yes	25.3	22.1	51.0	9.3 (8.0)	(7.5 - 9.0)	1477	10	820
	45	245/45 ZR 17	99 Y	XL	BSW	15492700000	Yes	25.7	24.5	51.0	9.6 (8.0)	(7.5 - 9.0)	1709	10	809
	50	205/50 ZR 17	93 W	XL	BSW	15492620000	Yes	25.1	20.9	51.0	8.4 (6.5)	(5.5 - 7.5)	1433	10	829
	50	215/50 ZR 17	95 W	XL	BSW	15492640000	Yes	25.5	23.1	51.0	8.9 (7.0)	(6.0 - 7.5)	1521	10	816
	50	225/50 ZR 17	94 W	SL	BSW	15492660000	Yes	25.9	22.4	51.0	9.2 (7.0)	(6.0 - 8.0)	1477	10	803
18	30	295/30 ZR 18	98 Y	XL	BSW	15492930000	Yes	25.0	25.2	51.0	11.9 (10.5)	(10.0 - 11.0)	1653	10	832
	35	245/35 ZR 18	92 Y	XL	BSW	15492800000	Yes	24.8	21.6	51.0	9.8 (8.5)	(8.0 - 9.5)	1389	10	839
	35	255/35 ZR 18	94 Y	XL	BSW	15492830000	Yes	25.0	22.9	51.0	10.2 (9.0)	(8.5 - 10.0)	1477	10	830
	35	265/35 ZR 18	97 Y	XL	BSW	15492870000	Yes	25.3	24.2	51.0	10.7 (9.5)	(9.0 - 10.5)	1609	10	821
	35	275/35 ZR 18	95 Y	SL	BSW	15492880000	Yes	25.6	25.4	51.0	10.9 (9.5)	(9.0 - 11.0)	1521	10	812
	35	285/35 ZR 18	101 Y	XL	BSW	15492920000	Yes	25.9	27.8	51.0	11.4 (10.0)	(9.5 - 11.0)	1819	10	803
	40	215/40 ZR 18	89 Y	XL	BSW	15492730000	Yes	24.8	20.0	51.0	8.6 (7.5)	(7.0 - 8.5)	1279	10	839
	40	225/40 ZR 18	92 Y	XL	BSW	15492750000	Yes	25.1	21.0	51.0	9.1 (8.0)	(7.5 - 9.0)	1389	10	828
	40	235/40 ZR 18	95 Y	XL	BSW	15492770000	Yes	25.4	22.2	51.0	9.5 (8.5)	(8.0 - 9.5)	1521	10	818
	40	245/40 ZR 18	97 Y	XL	BSW	15492810000	Yes	25.7	25.8	51.0	9.8 (8.5)	(8.0 - 9.5)	1609	10	808
	40	255/40 ZR 18	99 Y	XL	BSW	15492840000	Yes	26.0	25.2	51.0	10.2 (9.0)	(8.5 - 10.0)	1709	10	798
	40	275/40 ZR 18	99 Y	SL	BSW	15492890000	Yes	26.7	27.0	51.0	10.9 (9.5)	(9.0 - 11.0)	1709	10	779
	40	285/40 ZR 18	101 Y	SL	BSW	15592020000	Yes	27.0	27.8	51.0	11.4 (10.0)	(9.5 - 11.0)	1819	10	770
	45	225/45 ZR 18	91 Y	SL	BSW	15492760000	Yes	26.0	22.2	51.0	8.9 (7.5)	(7.0 - 8.5)	1356	10	800
	45	245/45 ZR 18	100 Y	XL	BSW	15492820000	Yes	26.7	24.3	51.0	9.6 (8.0)	(7.5 - 9.0)	1764	10	779
45	255/45 ZR 18	103 Y	XL	BSW	15492860000	Yes	27.0	28.0	51.0	10.0 (8.5)	(8.0 - 9.5)	1929	10	768	
50	235/50 ZR 18	97 Y	SL	BSW	15492780000	Yes	27.3	25.8	51.0	9.6 (7.5)	(6.5 - 8.5)	1609	10	762	
19	30	295/30 ZR 19	100 Y	XL	BSW	15494490000	Yes	26.0	27.4	51.0	11.9 (10.5)	(10.0 - 11.0)	1764	10	800
	30	305/30 ZR 19	102 Y	XL	BSW	15494500000	Yes	26.2	27.5	51.0	12.3 (11.0)	(10.5 - 11.5)	1874	10	793
	35	235/35 ZR 19	91 Y	XL	BSW	15492980000	Yes	25.5	22.1	51.0	9.5 (8.5)	(8.0 - 9.5)	1356	10	815
	35	245/35 ZR 19	93 Y	XL	BSW	15492990000	Yes	25.8	22.5	51.0	9.8 (8.5)	(8.0 - 9.5)	1433	10	807
	35	255/35 ZR 19	96 Y	XL	BSW	15494270000	Yes	26.0	24.2	51.0	10.2 (9.0)	(8.5 - 10.0)	1565	10	798
	35	265/35 ZR 19	98 Y	XL	BSW	15494360000	Yes	26.3	25.3	51.0	10.7 (9.5)	(9.0 - 10.5)	1653	10	790
	35	275/35 ZR 19	100 Y	XL	BSW	15494440000	Yes	26.6	27.9	51.0	10.9 (9.5)	(9.0 - 11.0)	1764	10	782
	35	285/35 ZR 19	99 Y	SL	BSW	15494480000	Yes	26.9	27.4	51.0	11.4 (10.0)	(9.5 - 11.0)	1709	10	774
	40	225/40 ZR 19	93 Y	XL	BSW	15492940000	Yes	26.1	21.1	51.0	9.1 (8.0)	(7.5 - 9.0)	1433	10	796
	40	245/40 ZR 19	98 Y	XL	BSW	15493010000	Yes	26.7	25.1	51.0	9.8 (8.5)	(8.0 - 9.5)	1653	10	778

BSW = Black Sidewall



G-MAX™ RS | Product Data

PASSENGER & CROSSOVER | SUMMER | ULTRA-HIGH PERFORMANCE

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ND S)	REVS PER MILE
19	40	255/40 ZR 19	100 Y	XL	BSW	15494300000	Yes	27.0	25.5	51.0	10.2 (9.0)	(8.5 - 10.0)	1764	10	769
	45	225/45 ZR 19	92 Y	SL	BSW	15492950000	Yes	27.0	23.4	51.0	8.9 (7.5)	(7.0 - 8.5)	1389	10	770
	45	245/45 ZR 19	102 Y	XL	BSW	15494240000	Yes	27.7	26.2	51.0	9.6 (8.0)	(7.5 - 9.0)	1874	10	750
20	35	275/35 ZR 20	102 Y	XL	BSW	15494570000	Yes	27.6	27.2	51.0	10.9 (9.5)	(9.0 - 11.0)	1874	10	753
	35	285/35 ZR 20	100 Y	SL	BSW	15501340000	Yes	27.9	28.7	51.0	11.4 (10.0)	(9.5 - 11.0)	1764	10	746
	35	305/35 ZR 20	104 Y	SL	BSW	15501350000	Yes	28.4	32.8	51.0	12.3 (11.0)	(10.0 - 12.0)	1984	10	731
	40	245/40 ZR 20	99 Y	XL	BSW	15494510000	Yes	27.7	27.7	51.0	9.8 (8.5)	(8.0 - 9.5)	1709	10	750
	40	275/40 ZR 20	106 Y	XL	BSW	15494590000	Yes	28.7	29.7	51.0	10.9 (9.5)	(9.0 - 11.0)	2094	10	725
	45	245/45 ZR 20	103 Y	XL	BSW	15494540000	Yes	28.7	26.9	51.0	9.6 (8.0)	(7.5 - 9.0)	1929	10	724

BSW = Black Sidewall

GENERAL TIRE  TM

DELIVERS



PASSENGER & CROSSOVER | ALL-SEASON | ULTRA-HIGH PERFORMANCE

G-MAX™ AS05

Rim Diameter



16" - 22"

Aspect Ratio



35 - 55

Tread Pattern



Asymmetric

TREADWEAR	TRACTION	TEMPERATURE	SPEED	WARRANTY
500 (LI ≤ 103)	AA	A	W	50,000 Miles
500 (LI ≥ 104)	A	A	W	50,000 Miles

Benefits

- Excellent size lineup with 59 sizes, covering 92% of the segment
- Superior handling on wet and dry roads
- Optimal traction in light snow
- Low road noise
- Long-lasting treadwear



Replacement Tire Monitor

Letters in the tread wear off to read "REPLACE TIRE" when the tire wears to 2/32 of tread depth, indicating a tire change is needed.



Visual Alignment Indicators

Indicators in both sides of the tread wear off evenly, ensuring the driver of proper alignment, or wear off unevenly, alerting the driver to check the wheel alignment.

Sample Vehicle Fitments Include:

- Audi A4
- BMW: 3 & 5 Series
- Chevrolet Camaro
- Dodge: Challenger & Charger
- Ford Mustang
- Mazda: 3, 6 & Miata MX5
- Mercedes-Benz: C & E-Class
- Mini Cooper
- Nissan: 350Z, 370Z & Maxima



CUSTOMER SATISFACTION TRIAL

Or the first 2/32^{nds} of tread. See warranty manual for complete details.

G-MAX™ AS⁰⁵ | Product Data

PASSENGER & CROSSOVER | ALL-SEASON | ULTRA-HIGH PERFORMANCE

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ^{nds})	REVS PER MILE
16	45	205/45 ZR 16	83 W	SL	BSW	15509530000	Yes	23.3	19.0	51.0	8.1 (7.0)	(6.5 - 7.5)	1074	10	893
	50	195/50 ZR 16	84 W	SL	BSW	15509520000	Yes	23.7	17.7	51.0	7.9 (6.0)	(5.5 - 7.0)	1102	10	877
	50	205/50 ZR 16	87 W	SL	BSW	15509540000	Yes	24.1	19.3	51.0	8.4 (6.5)	(5.5 - 7.5)	1201	10	863
	50	225/50 ZR 16	92 W	SL	BSW	15509570000	Yes	24.9	22.3	51.0	9.2 (7.0)	(6.0 - 8.0)	1389	10	836
	55	205/55 ZR 16	91 W	SL	BSW	15509550000	Yes	24.9	20.0	51.0	8.4 (6.5)	(5.5 - 7.5)	1356	10	835
	55	215/55 ZR 16	93 W	SL	BSW	15509560000	Yes	25.3	20.8	51.0	8.9 (7.0)	(6.0 - 7.5)	1433	10	821
	55	225/55 ZR 16	95 W	SL	BSW	15509580000	Yes	25.7	22.9	51.0	9.2 (7.0)	(6.0 - 8.0)	1521	10	807
17	40	205/40 ZR 17	84 W	XL	BSW	15509590000	Yes	23.5	17.2	51.0	8.3 (7.5)	(7.0 - 8.0)	1102	10	886
	40	245/40 ZR 17	91 W	SL	BSW	15509720000	Yes	24.7	22.4	51.0	9.8 (8.5)	(8.0 - 9.5)	1356	10	840
	40	275/40 ZR 17	98 W	SL	BSW	15509750000	Yes	25.7	25.3	51.0	10.9 (9.5)	(9.0 - 11.0)	1653	10	810
	45	205/45 ZR 17	88 W	XL	BSW	15509600000	Yes	24.3	19.0	50.0	8.1 (7.0)	(6.5 - 7.5)	1235	10	856
	45	215/45 ZR 17	91 W	XL	BSW	15509620000	Yes	24.6	21.3	51.0	8.4 (7.0)	(7.0 - 8.0)	1356	10	844
	45	225/45 ZR 17	91 W	SL	BSW	15509650000	Yes	25.0	21.4	51.0	8.9 (7.5)	(7.0 - 8.5)	1356	10	832
	45	235/45 ZR 17	94 W	SL	BSW	15509690000	Yes	25.3	22.1	51.0	9.3 (8.0)	(7.5 - 9.0)	1477	10	820
	45	245/45 ZR 17	99 W	XL	BSW	15509730000	Yes	25.7	23.7	51.0	9.6 (8.0)	(7.5 - 9.0)	1709	10	809
	50	205/50 ZR 17	93 W	XL	BSW	15509610000	Yes	25.1	20.6	51.0	8.4 (6.5)	(5.5 - 7.5)	1433	10	829
	50	215/50 ZR 17	95 W	XL	BSW	15509630000	Yes	25.5	22.5	51.0	8.9 (7.0)	(6.0 - 7.5)	1521	10	816
	50	225/50 ZR 17	94 W	SL	BSW	15509660000	Yes	25.9	21.4	51.0	9.2 (7.0)	(6.0 - 8.0)	1477	10	803
	50	235/50 ZR 17	96 W	SL	BSW	15509700000	Yes	26.3	24.1	51.0	9.6 (7.5)	(6.5 - 8.5)	1565	10	791
	50	245/50 ZR 17	99 W	SL	BSW	15509740000	Yes	26.6	26.0	51.0	10.0 (7.5)	(7.0 - 8.5)	1709	10	780
	55	215/55 ZR 17	94 W	SL	BSW	15509640000	Yes	26.3	22.3	51.0	8.9 (7.0)	(6.0 - 7.5)	1477	10	790
	55	225/55 ZR 17	97 W	SL	BSW	15509670000	Yes	26.7	24.1	51.0	9.2 (7.0)	(6.0 - 8.0)	1609	10	777
55	235/55 ZR 17	99 W	SL	BSW	15509710000	Yes	27.2	27.7	51.0	9.6 (7.5)	(6.5 - 8.5)	1709	10	764	
18	35	255/35 ZR 18	94 W	XL	BSW	15509870000	Yes	25.0	22.6	51.0	10.2 (9.0)	(8.5 - 10.0)	1477	10	830
	35	265/35 ZR 18	97 W	XL	BSW	15509900000	Yes	25.3	23.9	51.0	10.7 (9.5)	(9.0 - 10.5)	1609	10	821
	40	215/40 ZR 18	89 W	XL	BSW	15509760000	Yes	24.8	19.8	51.0	8.6 (7.5)	(7.0 - 8.5)	1279	10	839
	40	225/40 ZR 18	92 W	XL	BSW	15509780000	Yes	25.1	23.1	51.0	9.1 (8.0)	(7.5 - 9.0)	1389	10	828
	40	235/40 ZR 18	95 W	XL	BSW	15509810000	Yes	25.4	22.1	51.0	9.5 (8.5)	(8.0 - 9.5)	1521	10	818
	40	245/40 ZR 18	97 W	XL	BSW	15509840000	Yes	25.7	23.7	51.0	9.8 (8.5)	(8.0 - 9.5)	1609	10	808
	40	255/40 ZR 18	99 W	XL	BSW	15509880000	Yes	26.0	25.1	51.0	10.2 (9.0)	(8.5 - 10.0)	1709	10	798
	40	275/40 ZR 18	99 W	SL	BSW	15509910000	Yes	26.7	27.4	51.0	10.9 (9.5)	(9.0 - 11.0)	1709	10	779
	45	215/45 ZR 18	93 W	XL	BSW	15509770000	Yes	25.6	22.1	51.0	8.4 (7.0)	(7.0 - 8.0)	1433	10	811
	45	225/45 ZR 18	91 W	SL	BSW	15509790000	Yes	26.0	23.8	51.0	8.9 (7.5)	(7.0 - 8.5)	1356	10	800
	45	235/45 ZR 18	98 W	XL	BSW	15509820000	Yes	26.3	25.7	51.0	9.3 (8.0)	(7.5 - 9.0)	1653	10	789
	45	245/45 ZR 18	100 W	XL	BSW	15509850000	Yes	26.7	24.5	51.0	9.6 (8.0)	(7.5 - 9.0)	1764	10	779
	45	255/45 ZR 18	103 W	XL	BSW	15509890000	Yes	27.0	26.5	51.0	10.0 (8.5)	(8.0 - 9.5)	1929	10	768
	50	225/50 ZR 18	95 W	SL	BSW	15509800000	Yes	26.9	23.3	51.0	9.2 (7.0)	(6.0 - 8.0)	1521	10	773
	50	235/50 ZR 18	97 W	SL	BSW	15509830000	Yes	27.3	24.5	51.0	9.6 (7.5)	(6.5 - 8.5)	1609	10	762
55	245/55 ZR 18	103 W	SL	BSW	15509860000	Yes	28.6	28.8	51.0	10.0 (7.5)	(7.0 - 8.5)	1929	10	726	
19	35	245/35 ZR 19	93 W	XL	BSW	15575510000	Yes	25.8	23.0	51.0	9.8 (8.5)	(8.0 - 9.5)	1433	10	807

BSW = Black Sidewall



G-MAX™ AS⁰⁵ | Product Data

PASSENGER & CROSSOVER | ALL-SEASON | ULTRA-HIGH PERFORMANCE

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ND S)	REVS PER MILE
19	35	255/35 ZR 19	96 W	XL	BSW	15492320000	Yes	26.0	24.4	51.0	10.2 (9.0)	(8.5 - 10.0)	1565	10	798
	35	275/35 ZR 19	100 W	XL	BSW	15575270000	Yes	26.6	25.8	51.0	10.9 (9.5)	(9.0 - 11.0)	1764	10	782
	35	285/35 ZR 19	103 W	XL	BSW	15575550000	Yes	26.9	26.8	51.0	11.4 (10.0)	(9.5 - 11.0)	1929	10	774
	40	225/40 ZR 19	93 W	XL	BSW	15509930000	Yes	26.1	21.6	51.0	9.1 (8.0)	(7.5 - 9.0)	1433	10	796
	40	235/40 ZR 19	96 W	XL	BSW	15575260000	Yes	26.4	24.7	51.0	9.5 (8.5)	(8.0 - 9.5)	1565	10	787
	40	245/40 ZR 19	98 W	XL	BSW	15509950000	Yes	26.7	25.1	51.0	9.8 (8.5)	(8.0 - 9.5)	1653	10	778
	40	255/40 ZR 19	100 W	XL	BSW	15509970000	Yes	27.0	25.8	51.0	10.2 (9.0)	(8.5 - 10.0)	1764	10	769
	40	275/40 ZR 19	101 W	SL	BSW	15492340000	Yes	27.7	31.1	51.0	10.9 (9.5)	(9.0 - 11.0)	1819	10	751
	45	225/45 ZR 19	92 W	SL	BSW	15509940000	Yes	27.0	23.9	51.0	8.9 (7.5)	(7.0 - 8.5)	1389	10	770
	45	245/45 ZR 19	102 W	XL	BSW	15509960000	Yes	27.7	26.0	51.0	9.6 (8.0)	(7.5 - 9.0)	1874	10	750
	50	245/50 ZR 19	105 W	XL	BSW	15575520000	Yes	28.6	29.2	51.0	10.0 (7.5)	(7.0 - 8.5)	2039	10	725
	50	255/50 ZR 19	107 W	XL	BSW	15575530000	Yes	29.0	31.8	51.0	10.4 (8.0)	(7.0 - 9.0)	2149	10	715
	55	235/55 ZR 19	105 W	XL	BSW	15575480000	Yes	29.2	27.7	51.0	9.6 (7.5)	(6.5 - 8.5)	2039	10	712
20	35	245/35 ZR 20	95 W	XL	BSW	15492350000	Yes	26.8	24.6	51.0	9.8 (8.5)	(8.0 - 9.5)	1521	10	777
	35	255/35 ZR 20	97 W	XL	BSW	15492380000	Yes	27.0	24.1	51.0	10.2 (9.0)	(8.5 - 10.0)	1609	10	769
	35	275/35 ZR 20	102 W	XL	BSW	15492420000	Yes	27.6	28.5	51.0	10.9 (9.5)	(9.0 - 11.0)	1874	10	753
	35	285/35 ZR 20	100 W	SL	BSW	15575560000	Yes	27.9	27.5	51.0	11.4 (10)	(9.5 - 11)	1764	10	746
	35	305/35 ZR 20	104 W	SL	BSW	15590670000	Yes	28.4	30.0	51.0	12.3 (11.0)	(10.0 - 12.0)	1984	10	731
	40	245/40 ZR 20	99 W	XL	BSW	15492360000	Yes	27.7	27.5	51.0	9.8 (8.5)	(8.0 - 9.5)	1709	10	750
	40	275/40 ZR 20	106 W	XL	BSW	15492450000	Yes	28.7	30.3	51.0	10.9 (9.5)	(9.0 - 11.0)	2094	10	725
	45	245/45 ZR 20	103 W	XL	BSW	15492370000	Yes	28.7	27.1	51.0	9.6 (8.0)	(7.5 - 9.0)	1929	10	724
45	255/45 ZR 20	105 W	XL	BSW	15492390000	Yes	29.0	28.7	51.0	10.0 (8.5)	(8.0 - 9.5)	2039	10	715	
22	40	265/40 ZR 22	106 W	XL	BSW	15492470000	Yes	30.3	33.8	51.0	10.7 (9.5)	(9.0 - 10.5)	2094	10	685

BSW = Black Sidewall

GENERAL TIRE  TM

DELIVERS



CROSSOVER & LT/SUV | ALL-SEASON | ULTRA-HIGH PERFORMANCE

GRABBER™ UHP

Rim Diameter



16" - 24"

Aspect Ratio



35 - 65

Tread Pattern



Directional

Sample Vehicle Fitments Include:

- BMW: X5 & Pickup Truck (Tuning Fitments)
- Cadillac Escalade
- Chevrolet Suburban
- Nissan Murano
- Toyota 4Runner

TREADWEAR	TRACTION	TEMPERATURE	SPEED
320	A	A	H, V & W
360	A	A	H, V & W

Benefits

- Superior handling on wet and dry roads
- Excellent dry and wet braking
- Low road noise
- Long-lasting treadwear



CUSTOMER SATISFACTION TRIAL

Or the first 2/32^{nds} of tread. See warranty manual for complete details.

GRABBER™ UHP | Product Data

CROSSOVER & LT/SUV | ALL-SEASON | ULTRA-HIGH PERFORMANCE

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ^{nds})	REVS PER MILE
16	65	255/65 R 16	109 H	SL	BSW	15477130000	No	29.1	31.2	51.0	10.2 (7.5)	(7.0 - 9.0)	2271	11	715
17	55	275/55 R 17	109 V	SL	BSW	15477210000	Yes	28.9	32.6	51.0	11.2 (8.5)	(7.5 - 9.5)	2271	10	719
	60	255/60 R 17	106 V	SL	BSW	15477170000	No	29.0	30.9	51.0	10.2 (7.5)	(7.0 - 9.0)	2094	11	715
18	55	255/55 R 18	109 W	XL	BSW	15477200000	Yes	29.0	30.4	51.0	10.4 (8.0)	(7.0 - 9.0)	2271	10	715
19	55	255/55 R 19	111 V	XL	BSW	04501900000	Yes	30.0	33.7	51.0	10.4 (8.0)	(7.0 - 9.0)	2403	10	691
20	45	295/45 R 20	114 V	XL	BSW	15477900000	Yes	30.5	38.2	51.0	11.7 (10.0)	(9.5 - 11.0)	2601	10	682
	50	295/50 R 20	118 V	XL	BSW	15477930000	Yes	31.6	40.8	51.0	12.2 (9.5)	(8.0 - 10.5)	2910	10	657
	55	275/55 R 20	117 V	XL	BSW	15477910000	Yes	31.9	38.0	51.0	11.2 (8.5)	(7.5 - 9.5)	2833	10	651
22	40	305/40 R 22	114 V	XL	BSW	15477920000	Yes	31.6	37.0	51.0	12.3 (11.0)	(10.0 - 12.0)	2601	10	657
	45	305/45 R 22	118 V	XL	BSW	15478020000	Yes	32.8	42.7	51.0	11.9 (10.0)	(9.5 - 11.5)	2910	10	633
23	40	305/40 R 23	115 V	XL	BSW	15477870000	Yes	32.6	40.9	51.0	12.3 (11.0)	(10.0 - 12.0)	2679	10	637
24	35	305/35 R 24	112 V	XL	BSW	15447940000	Yes	32.4	40.5	51.0	12.3 (11.0)	(10.0 - 12.0)	2469	10	641

BSW = Black Sidewall





DELIVERS

for excelling year-round.

Our **touring** products are developed to provide confidence in all driving conditions year-round.



AltiMAX™ RT⁴⁵



AltiMAX™ 365 AW



Grabber™ HTS⁶⁰





PASSENGER & CROSSOVER | ALL-SEASON | TOURING

ALTIMAX™ RT45

Rim Diameter



14" - 20"

Aspect Ratio



40 - 70

Tread Pattern



Symmetric

TREADWEAR	TRACTION	TEMPERATURE	SPEED	WARRANTY
600	A	B	T	75,000 Miles (14" - 15")
600	A	A	H	75,000 Miles (14" - 15")
600	A	A	V	65,000 Miles (14" - 15")
700	A	B	T	75,000 Miles (16" - 20")
700	A	A	H	75,000 Miles (16" - 20")
700	A	A	V	65,000 Miles (16" - 20")


Benefits

- Expansive size lineup with 136 sizes, covering more than 85% of the segment
- Reliable braking on wet roads
- Responsive handling on wet and dry roads
- Optimal traction in light snow
- Low road noise
- Long-lasting treadwear



CUSTOMER SATISFACTION TRIAL

Or the first 2/32^{nds} of tread. See warranty manual for complete details.



Replacement Tire Monitor

Letters in the tread wear off to read "REPLACE TIRE" when the tire wears to 2/32 of tread depth, indicating a tire change is needed.



Visual Alignment Indicators

Indicators in both sides of the tread wear off evenly, ensuring the driver of proper alignment, or wear off unevenly, alerting the driver to check the wheel alignment.

Sample Vehicle Fitments Include:

- Chevrolet: Bolt EV, Malibu
- Dodge: Grand Caravan, Journey
- Ford: Edge, Focus
- Honda: Accord, Civic, Odyssey
- Jeep Compass
- Kia: Carnival, Optima, Soul
- Mazda CRX 5
- Nissan: Murano, Sentra
- Subaru Outback
- Toyota: Camry, Sienna

ALTIMAX™ RT45 | Product Data

PASSENGER & CROSSOVER | ALL-SEASON | TOURING

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ND PS)	REVS PER MILE
14	60	185/60 R 14	82 H	SL	BSW	15576020000	No	22.7	14.4	51.0	7.4 (5.5)	(5.0 - 6.5)	1047	11	914
	60	195/60 R 14	86 H	SL	BSW	15577250000	No	23.2	16.0	51.0	7.9 (6.0)	(5.5 - 7.0)	1168	11	895
	65	175/65 R 14	82 T	SL	BSW	15575970000	No	23.0	14.3	44.0	7.0 (5.0)	(5.0 - 6.0)	1047	11	905
	65	185/65 R 14	86 H	SL	BSW	15576060000	No	23.5	15.1	51.0	7.4 (5.5)	(5.0 - 6.5)	1168	11	885
	65	185/65 R 14	86 T	SL	BSW	15576050000	No	23.5	14.9	44.0	7.4 (5.5)	(5.0 - 6.5)	1168	11	885
	70	175/70 R 14	84 T	SL	BSW	15575990000	No	23.6	14.3	44.0	7.0 (5.0)	(4.5 - 6.0)	1102	11	879
	70	185/70 R 14	88 T	SL	BSW	15576100000	No	24.2	15.6	44.0	7.4 (5.5)	(4.5 - 6.0)	1235	11	859
	70	195/70 R 14	91 T	SL	BSW	15577260000	No	24.7	17.3	44.0	7.9 (6.0)	(5.0 - 6.5)	1356	11	839
	70	205/70 R 14	98 T	XL	BSW	15577330000	No	25.3	19.6	51.0	8.2 (6.0)	(5.0 - 7.0)	1653	11	821
	70	215/70 R 14	96 T	SL	BSW	15577410000	No	25.9	20.5	44.0	8.7 (6.5)	(5.5 - 7.0)	1565	11	804
15	70	225/70 R 14	99 T	SL	OWL	15576530000	No	26.4	23.2	44.0	9.0 (6.5)	(6.0 - 7.5)	1709	11	787
	55	185/55 R 15	82 H	SL	BSW	15576000000	Yes	23.0	15.9	51.0	7.6 (6.0)	(5.0 - 6.5)	1047	11	903
	55	185/55 R 15	82 V	SL	BSW	15577190000	Yes	23.0	15.6	51.0	7.6 (6.0)	(5.0 - 6.5)	1047	11	903
	55	195/55 R 15	85 V	SL	BSW	15577230000	Yes	23.4	16.5	51.0	7.9 (6.0)	(5.5 - 7.0)	1135	11	886
	60	185/60 R 15	84 H	SL	BSW	15576040000	No	23.7	16.6	51.0	7.4 (5.5)	(5.0 - 6.5)	1102	11	875
	60	185/60 R 15	84 T	SL	BSW	15576030000	No	23.7	16.6	44.0	7.4 (5.5)	(5.0 - 6.5)	1102	11	875
	60	195/60 R 15	88 H	SL	BSW	15576130000	No	24.2	17.0	51.0	7.9 (6.0)	(5.5 - 7.0)	1235	11	858
	60	195/60 R 15	88 T	SL	BSW	15576120000	No	24.2	17.0	44.0	7.9 (6.0)	(5.5 - 7.0)	1235	11	858
	60	205/60 R 15	91 H	SL	BSW	15577310000	No	24.7	18.7	51.0	8.2 (6.0)	(5.5 - 7.5)	1356	11	842
	60	215/60 R 15	94 T	SL	BSW	15577380000	No	25.2	19.4	44.0	8.7 (6.5)	(6.0 - 7.5)	1477	11	826
	60	225/60 R 15	96 H	SL	BSW	15577480000	No	25.6	21.8	51.0	9.0 (6.5)	(6.0 - 8.0)	1565	11	811
	65	175/65 R 15	84 H	SL	BSW	15575980000	No	24.0	14.7	51.0	7.0 (5.0)	(5.0 - 6.0)	1102	11	867
	65	185/65 R 15	88 H	SL	BSW	15576090000	No	24.5	15.9	51.0	7.4 (5.5)	(5.0 - 6.5)	1235	11	849
	65	185/65 R 15	88 T	SL	BSW	15576070000	No	24.5	15.9	44.0	7.4 (5.5)	(5.0 - 6.5)	1235	11	849
	65	195/65 R 15	91 H	SL	BSW	15576150000	No	25.0	17.1	51.0	7.9 (6.0)	(5.5 - 7.0)	1356	11	832
	65	195/65 R 15	91 T	SL	BSW	15576140000	No	25.0	17.1	44.0	7.9 (6.0)	(5.5 - 7.0)	1356	11	832
	65	205/65 R 15	94 H	SL	BSW	15576210000	No	25.5	18.7	51.0	8.2 (6.0)	(5.5 - 7.5)	1477	11	815
	65	205/65 R 15	99 T	XL	BSW	15576200000	No	25.5	19.8	51.0	8.2 (6.0)	(5.5 - 7.5)	1709	11	815
	65	215/65 R 15	96 T	SL	BSW	15577400000	No	26.0	20.9	44.0	8.7 (6.5)	(6.0 - 7.5)	1565	11	799
	70	205/70 R 15	96 T	SL	BSW	15576240000	No	26.3	20.7	44.0	8.2 (6.0)	(5.0 - 7.0)	1565	11	790
70	215/70 R 15	98 T	SL	BSW	15576350000	No	26.9	23.2	44.0	8.7 (6.5)	(5.5 - 7.0)	1653	11	774	
70	225/70 R 15	100 T	SL	OWL	15576540000	No	27.4	26.0	44.0	9.0 (6.5)	(6.0 - 7.5)	1764	11	758	
70	235/70 R 15	103 T	SL	OWL	15576670000	No	28.0	26.8	44.0	9.4 (7.0)	(6.0 - 8.0)	1929	11	743	
16	50	195/50 R 16	84 H	SL	BSW	15576110000	Yes	23.7	16.8	51.0	7.9 (6.0)	(5.5 - 7.0)	1102	11	877
	50	195/50 R 16	84 V	SL	BSW	15577650000	Yes	23.7	16.7	51.0	7.9 (6.0)	(5.5 - 7.0)	1102	11	877
	50	205/50 R 16	87 H	SL	BSW	15577280000	Yes	24.1	19.1	51.0	8.4 (6.5)	(5.5 - 7.5)	1201	11	863
	55	185/55 R 16	87 H	XL	BSW	15576010000	Yes	24.0	17.5	51.0	7.6 (6.0)	(5.0 - 6.5)	1201	11	865
	55	195/55 R 16	87 V	SL	BSW	15577240000	Yes	24.4	17.4	51.0	7.9 (6.0)	(5.5 - 7.0)	1201	11	850
	55	205/55 R 16	91 H	SL	BSW	15576170000	Yes	24.9	21.2	51.0	8.4 (6.5)	(5.5 - 7.5)	1356	11	835
	55	205/55 R 16	91 T	SL	BSW	15576160000	Yes	24.9	21.2	44.0	8.4 (6.5)	(5.5 - 7.5)	1356	11	835

BSW = Black Sidewall | OWL = Outlined White Letter



ALTIMAX™ RT45 | Product Data

PASSENGER & CROSSOVER | ALL-SEASON | TOURING

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ND S)	REVS PER MILE
16	55	205/55 R 16	91 V	SL	BSW	15577300000	Yes	24.9	19.9	51.0	8.4 (6.5)	(5.5 - 7.5)	1356	11	835
	55	215/55 R 16	97 H	XL	BSW	15576260000	Yes	25.3	22.3	51.0	8.9 (7.0)	(6.0 - 7.5)	1609	11	821
	55	225/55 R 16	95 H	SL	BSW	15577460000	Yes	25.7	21.1	51.0	9.2 (7.0)	(6.0 - 8.0)	1521	11	807
	60	185/60 R 16	86 H	SL	BSW	15577640000	No	24.7	16.5	51.0	7.4 (5.5)	(5.0 - 6.5)	1168	11	840
	60	205/60 R 16	92 H	SL	BSW	15576190000	No	25.7	18.8	51.0	8.2 (6.0)	(5.5 - 7.5)	1389	11	809
	60	205/60 R 16	92 T	SL	BSW	15576180000	No	25.7	19.2	44.0	8.2 (6.0)	(5.5 - 7.5)	1389	11	809
	60	205/60 R 16	92 V	SL	BSW	15577320000	No	25.7	18.6	51.0	8.2 (6.0)	(5.5 - 7.5)	1389	11	809
	60	215/60 R 16	95 H	SL	BSW	15576300000	No	26.2	21.2	51.0	8.7 (6.5)	(6.0 - 7.5)	1521	11	794
	60	215/60 R 16	95 T	SL	BSW	15576290000	No	26.2	21.1	44.0	8.7 (6.5)	(6.0 - 7.5)	1521	11	794
	60	215/60 R 16	95 V	SL	BSW	15577390000	No	26.2	20.9	51.0	8.7 (6.5)	(6.0 - 7.5)	1521	11	794
	60	225/60 R 16	98 H	SL	BSW	15576450000	No	26.6	22.1	51.0	9.0 (6.5)	(6.0 - 8.0)	1653	11	780
	60	225/60 R 16	98 T	SL	BSW	15576440000	No	26.6	22.1	44.0	9.0 (6.5)	(6.0 - 8.0)	1653	11	780
	60	235/60 R 16	100 H	SL	BSW	15576610000	No	27.1	23.9	51.0	9.4 (7.0)	(6.5 - 8.5)	1764	11	766
	60	235/60 R 16	100 T	SL	BSW	15576600000	No	27.1	23.9	44.0	9.4 (7.0)	(6.5 - 8.5)	1764	11	766
	65	205/65 R 16	95 H	SL	BSW	15576230000	No	26.5	19.7	51.0	8.2 (6.0)	(5.5 - 7.5)	1521	11	784
	65	205/65 R 16	95 T	SL	BSW	15576220000	No	26.5	19.7	44.0	8.2 (6.0)	(5.5 - 7.5)	1521	11	784
	65	215/65 R 16	98 H	SL	BSW	15576330000	No	27.0	21.5	51.0	8.7 (6.5)	(6.0 - 7.5)	1653	11	769
	65	215/65 R 16	98 T	SL	BSW	15576320000	No	27.0	21.1	44.0	8.7 (6.5)	(6.0 - 7.5)	1653	11	769
	65	225/65 R 16	100 H	SL	BSW	15576500000	No	27.5	22.7	51.0	9.0 (6.5)	(6.0 - 8.0)	1764	11	755
	65	225/65 R 16	100 T	SL	BSW	15576490000	No	27.5	22.7	44.0	9.0 (6.5)	(6.0 - 8.0)	1764	11	755
	65	235/65 R 16	103 T	SL	BSW	15576640000	No	28.0	25.4	44.0	9.4 (7.0)	(6.5 - 8.5)	1929	11	741
70	205/70 R 16	97 T	SL	BSW	15576250000	No	27.3	22.7	44.0	8.2 (6.0)	(5.0 - 7.0)	1609	11	761	
70	215/70 R 16	100 H	SL	BSW	15576360000	No	27.9	24.8	51.0	8.7 (6.5)	(5.5 - 7.0)	1764	11	746	
70	215/70 R 16	100 T	SL	BSW	15577420000	No	27.9	24.8	44.0	8.7 (6.5)	(5.5 - 7.0)	1764	11	746	
70	225/70 R 16	103 T	SL	BSW	15576550000	No	28.4	26.9	44.0	9.0 (6.5)	(6.0 - 7.5)	1929	11	731	
17	45	205/45 R 17	88 V	XL	BSW	15577270000	Yes	24.3	17.9	51.0	8.1 (7.0)	(6.5 - 7.5)	1235	11	856
	45	215/45 R 17	91 V	XL	BSW	15577350000	Yes	24.6	20.7	51.0	8.4 (7.0)	(7.0 - 8.0)	1356	11	844
	45	225/45 R 17	91 H	SL	BSW	15576370000	Yes	25.0	22.1	51.0	8.9 (7.5)	(7.0 - 8.5)	1356	11	832
	45	225/45 R 17	94 V	XL	BSW	15577430000	Yes	25.0	20.4	51.0	8.9 (7.5)	(7.0 - 8.5)	1477	11	832
	45	235/45 R 17	97 H	XL	BSW	15577490000	Yes	25.3	24.4	50.0	9.3 (8.0)	(7.5 - 9.0)	1609	11	820
	45	245/45 R 17	99 H	XL	BSW	15577570000	Yes	25.7	22.0	51.0	9.6 (8.0)	(7.5 - 9.0)	1709	11	809
	50	205/50 R 17	93 H	XL	BSW	15577660000	Yes	25.1	21.7	51.0	8.4 (6.5)	(5.5 - 7.5)	1433	11	829
	50	205/50 R 17	93 V	XL	BSW	15577290000	Yes	25.1	21.6	50.0	8.4 (6.5)	(5.5 - 7.5)	1433	11	829
	50	215/50 R 17	95 H	XL	BSW	15577670000	Yes	25.5	21.0	51.0	8.9 (7.0)	(6.0 - 7.5)	1521	11	816
	50	215/50 R 17	95 V	XL	BSW	15577360000	Yes	25.5	20.7	51.0	8.9 (7.0)	(6.0 - 7.5)	1521	11	816
	50	225/50 R 17	98 H	XL	BSW	15577720000	Yes	25.9	23.3	51.0	9.2 (7.0)	(6.0 - 8.0)	1653	11	803
	50	225/50 R 17	98 T	XL	BSW	15576380000	Yes	25.9	23.3	51.0	9.2 (7.0)	(6.0 - 8.0)	1653	11	803
	50	225/50 R 17	98 V	XL	BSW	15577450000	Yes	25.9	23.3	51.0	9.2 (7.0)	(6.0 - 8.0)	1653	11	803
	50	235/50 R 17	96 H	SL	BSW	15577740000	Yes	26.3	24.4	51.0	9.6 (7.5)	(6.5 - 8.5)	1565	11	791
	55	215/55 R 17	94 H	SL	BSW	15577680000	Yes	26.3	23.6	51.0	8.9 (7.0)	(6.0 - 7.5)	1477	11	790
	55	215/55 R 17	94 T	SL	BSW	15576270000	Yes	26.3	23.6	44.0	8.9 (7.0)	(6.0 - 7.5)	1477	11	790
	55	215/55 R 17	94 V	SL	BSW	15577370000	Yes	26.3	20.9	51.0	8.9 (7.0)	(6.0 - 7.5)	1477	11	790
	55	225/55 R 17	97 H	SL	BSW	15576410000	Yes	26.7	24.7	51.0	9.2 (7.0)	(6.0 - 8.0)	1609	11	777
	55	225/55 R 17	97 T	SL	BSW	15576400000	Yes	26.7	24.7	44.0	9.2 (7.0)	(6.0 - 8.0)	1609	11	777
	55	225/55 R 17	97 V	SL	BSW	15577470000	Yes	26.7	23.6	51.0	9.2 (7.0)	(6.0 - 8.0)	1609	11	777
	55	235/55 R 17	99 H	SL	BSW	15576580000	Yes	27.2	24.9	51.0	9.6 (7.5)	(6.5 - 8.5)	1709	11	764
55	235/55 R 17	99 T	SL	BSW	15576570000	Yes	27.2	24.9	44.0	9.6 (7.5)	(6.5 - 8.5)	1709	11	764	
60	215/60 R 17	96 T	SL	BSW	15576310000	No	27.2	21.4	44.0	8.7 (6.5)	(6.0 - 7.5)	1565	11	765	

BSW = Black Sidewall

ALTIMAX™ RT45 | Product Data

PASSENGER & CROSSOVER | ALL-SEASON | TOURING

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ^{nds})	REVS PER MILE
17	60	225/60 R 17	99 H	SL	BSW	15576470000	No	27.6	24.8	51.0	9.0 (6.5)	(6.0 - 8.0)	1709	11	752
	60	225/60 R 17	99 T	SL	BSW	15576460000	No	27.6	24.8	44.0	9.0 (6.5)	(6.0 - 8.0)	1709	11	752
	60	235/60 R 17	102 H	SL	BSW	15577550000	No	28.1	26.1	51.0	9.4 (7.0)	(6.5 - 8.5)	1874	11	739
	60	235/60 R 17	102 T	SL	BSW	15576620000	No	28.1	26.1	44.0	9.4 (7.0)	(6.5 - 8.5)	1874	11	739
	65	215/65 R 17	99 H	SL	BSW	15577700000	No	28.0	22.9	51.0	8.7 (6.5)	(6.0 - 7.5)	1709	11	742
	65	215/65 R 17	99 T	SL	BSW	15576340000	No	28.0	22.9	44.0	8.7 (6.5)	(6.0 - 7.5)	1709	11	742
	65	225/65 R 17	102 H	SL	BSW	15576520000	No	28.5	26.7	51.0	9.0 (6.5)	(6.0 - 8.0)	1874	11	729
	65	225/65 R 17	102 T	SL	BSW	15576510000	No	28.5	26.7	44.0	9.0 (6.5)	(6.0 - 8.0)	1874	11	729
	65	235/65 R 17	104 H	SL	BSW	15577770000	No	29.0	27.4	51.0	9.4 (7.0)	(6.5 - 8.5)	1984	11	716
65	235/65 R 17	104 T	SL	BSW	15576650000	No	29.0	27.4	44.0	9.4 (7.0)	(6.5 - 8.5)	1984	11	716	
18	40	225/40 R 18	92 V	XL	BSW	15577710000	Yes	25.1	21.6	50.0	9.1 (8.0)	(7.5 - 9.0)	1389	11	828
	40	245/40 R 18	97 V	XL	BSW	15577620000	Yes	25.7	21.9	51.0	9.8 (8.5)	(8.0 - 9.5)	1609	11	808
	45	225/45 R 18	95 V	XL	BSW	15577440000	Yes	26.0	22.4	51.0	8.9 (7.5)	(7.0 - 8.5)	1521	11	800
	45	235/45 R 18	98 V	XL	BSW	15577500000	Yes	26.3	23.4	51.0	9.3 (8.0)	(7.5 - 9.0)	1653	11	789
	45	245/45 R 18	100 V	XL	BSW	15577580000	Yes	26.7	23.0	51.0	9.6 (8.0)	(7.5 - 9.0)	1764	11	779
	50	225/50 R 18	95 H	SL	BSW	15577730000	Yes	26.9	22.4	51.0	9.2 (7.0)	(6.0 - 8.0)	1521	11	773
	50	225/50 R 18	95 T	SL	BSW	15576390000	Yes	26.9	22.4	44.0	9.2 (7.0)	(6.0 - 8.0)	1521	11	773
	50	235/50 R 18	97 H	SL	BSW	15576560000	Yes	27.3	23.9	51.0	9.6 (7.5)	(6.5 - 8.5)	1609	11	762
	50	235/50 R 18	97 V	SL	BSW	15577520000	Yes	27.3	23.9	51.0	9.6 (7.5)	(6.5 - 8.5)	1609	11	762
	50	245/50 R 18	100 V	SL	BSW	15577800000	Yes	27.6	24.4	51.0	10.0 (7.5)	(7.0 - 8.5)	1764	11	751
	55	215/55 R 18	95 H	SL	BSW	15577690000	Yes	27.3	23.7	51.0	8.9 (7.0)	(6.0 - 7.5)	1521	11	761
	55	215/55 R 18	95 T	SL	BSW	15576280000	Yes	27.3	23.7	44.0	8.9 (7.0)	(6.0 - 7.5)	1521	11	761
	55	225/55 R 18	98 H	SL	BSW	15576420000	Yes	27.7	25.2	51.0	9.2 (7.0)	(6.0 - 8.0)	1653	11	749
	55	235/55 R 18	100 H	SL	BSW	15576590000	Yes	28.2	25.4	51.0	9.6 (7.5)	(6.5 - 8.5)	1764	11	737
	55	235/55 R 18	100 T	SL	BSW	15577750000	Yes	28.2	26.4	44.0	9.6 (7.5)	(6.5 - 8.5)	1764	11	737
	55	235/55 R 18	104 V	XL	BSW	15577530000	Yes	28.2	26.0	51.0	9.6 (7.5)	(6.5 - 8.5)	1984	11	737
	55	245/55 R 18	103 T	SL	BSW	15576690000	Yes	28.6	28.7	44.0	10.0 (7.5)	(7.0 - 8.5)	1929	11	726
	60	225/60 R 18	100 H	SL	BSW	15576480000	No	28.6	24.6	51.0	9.0 (6.5)	(6.0 - 8.0)	1764	11	726
	60	235/60 R 18	107 H	XL	BSW	15577760000	No	29.1	27.1	51.0	9.4 (7.0)	(6.5 - 8.5)	2149	11	714
	60	235/60 R 18	107 T	XL	BSW	15576630000	No	29.1	27.3	51.0	9.4 (7.0)	(6.5 - 8.5)	2149	11	714
60	235/60 R 18	107 V	XL	BSW	15577560000	No	29.1	27.2	51.0	9.4 (7.0)	(6.5 - 8.5)	2149	11	714	
65	235/65 R 18	106 H	SL	BSW	15577780000	No	30.0	28.7	51.0	9.4 (7.0)	(6.5 - 8.5)	2094	11	692	
65	235/65 R 18	106 T	SL	BSW	15576660000	No	30.0	28.7	44.0	9.4 (7.0)	(6.5 - 8.5)	2094	11	692	
19	40	235/40 R 19	96 V	XL	BSW	15577200000	Yes	26.4	23.0	51.0	9.5 (8.5)	(8.0 - 9.5)	1565	11	787
	40	245/40 R 19	98 V	XL	BSW	15577630000	Yes	26.7	24.4	51.0	9.8 (8.5)	(8.0 - 9.5)	1653	11	778
	45	235/45 R 19	95 H	SL	BSW	15577510000	Yes	27.3	25.4	51.0	9.3 (8.0)	(7.5 - 9.0)	1521	11	760
	45	245/45 R 19	102 V	XL	BSW	15577590000	Yes	27.7	25.9	51.0	9.6 (8.0)	(7.5 - 9.0)	1874	11	750
	45	255/45 R 19	104 V	XL	BSW	15577610000	Yes	28.0	25.5	51.0	10.0 (8.5)	(8.0 - 9.5)	1984	11	741
	50	235/50 R 19	99 H	SL	BSW	15577210000	Yes	28.3	24.8	51.0	9.6 (7.5)	(6.5 - 8.5)	1709	11	735
	55	225/55 R 19	99 H	SL	BSW	15576430000	Yes	28.7	26.4	51.0	9.2 (7.0)	(6.0 - 8.0)	1709	11	723
	55	235/55 R 19	101 H	SL	BSW	15577830000	Yes	29.2	26.8	51.0	9.6 (7.5)	(6.5 - 8.5)	1819	11	712
	55	235/55 R 19	105 V	XL	BSW	15577540000	Yes	29.2	26.3	51.0	9.6 (7.5)	(6.5 - 8.5)	2039	11	712
	55	245/55 R 19	103 H	SL	BSW	15577820000	Yes	29.6	30.2	51.0	10.0 (7.5)	(7.0 - 8.5)	1929	11	702
20	40	245/40 R 20	99 V	XL	BSW	15577790000	Yes	27.7	25.1	51.0	9.8 (8.5)	(8.0 - 9.5)	1709	11	750
	45	245/45 R 20	99 V	SL	BSW	15577600000	Yes	28.7	25.2	51.0	9.6 (8.0)	(7.5 - 9.0)	1709	11	724
	50	245/50 R 20	105 H	XL	BSW	15576680000	Yes	29.6	29.3	51.0	10.0 (7.5)	(7.0 - 8.5)	2039	11	701
	50	245/50 R 20	105 V	XL	BSW	15577810000	Yes	29.6	28.2	51.0	10.0 (7.5)	(7.0 - 8.5)	2039	11	701
	55	235/55 R 20	102 H	SL	BSW	15577840000	Yes	30.2	29.0	51.0	9.6 (7.5)	(6.5 - 8.5)	1874	11	688

BSW = Black Sidewall



PASSENGER & CROSSOVER | ALL-WEATHER | TOURING

ALTIMAX™ 365 AW

Rim Diameter



15" - 20"

Aspect Ratio



40 - 70

Tread Pattern



Symmetric

TREADWEAR	TRACTION	TEMPERATURE	SPEED	WARRANTY
640	A	A	H	60,000 Miles
540	A	A	V	60,000 Miles

Benefits

- Symmetric tread pattern allows for the tire to be rotated, promoting long, even tread life
- Best-in-class all-around performance*
- Confident driving in all weather conditions
- Balanced performance on wet and dry roads
- Optimal traction in deep snow



Visual Alignment Indicators

Indicators in both sides of the tread wear off evenly, ensuring the driver of proper alignment, or wear off unevenly, alerting the driver to check the wheel alignment.



3-Peak Mountain Snowflake

Meets the severe snow service requirements of the U.S. Tire Manufacturers Association (USTMA) and the Tire and Rubber Association of Canada (TRAC).

Sample Vehicle Fitments Include:

- Acura
- BMW
- Cadillac
- Chevrolet
- Fiat
- Ford
- Honda
- Hyundai
- Kia
- Lexus
- Mazda
- Nissan
- Subaru
- Toyota
- Volkswagen



CUSTOMER SATISFACTION TRIAL

Or the first 2/32^{nds} of tread. See warranty manual for complete details.

*Based on internal tire test results of the following key performance categories: dry handling, wet handling, comfort, snow traction, and ice braking, compared to Firestone WeatherGrip, Nokian WR G4 & Toyo Celsius in the size 205/65R16. On road results may vary.

ALTIMAX™ 365 AW | Product Data

PASSENGER & CROSSOVER | ALL-WEATHER | TOURING

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ^{nds})	REVS PER MILE
15	55	185/55 R 15	82 H	SL	BSW	15574920000	Yes	23.0	16.6	51.0	7.6 (6.0)	(5.0 - 6.5)	1047	11	903
	60	185/60 R 15	84 H	SL	BSW	15574790000	No	23.7	16.9	51.0	7.4 (5.5)	(5.0 - 6.5)	1102	11	875
	60	195/60 R 15	88 H	SL	BSW	15574640000	No	24.2	17.7	51.0	7.9 (6.0)	(5.5 - 7.0)	1235	11	858
	65	175/65 R 15	84 H	SL	BSW	15574850000	No	24.0	15.7	51.0	7.0 (5.0)	(5.0 - 6.0)	1102	11	867
	65	185/65 R 15	88 H	SL	BSW	15574570000	No	24.5	16.3	51.0	7.4 (5.5)	(5.0 - 6.5)	1235	11	849
	65	195/65 R 15	91 H	SL	BSW	15574410000	No	25.0	17.8	51.0	7.9 (6.0)	(5.5 - 7.0)	1356	11	832
16	55	205/55 R 16	91 H	SL	BSW	15574400000	Yes	24.9	21.7	51.0	8.4 (6.5)	(5.5 - 7.5)	1356	11	835
	55	215/55 R 16	97 H	XL	BSW	15574690000	Yes	25.3	22.6	51.0	8.9 (7.0)	(6.0 - 7.5)	1609	11	821
	60	205/60 R 16	92 V	SL	BSW	15574490000	No	25.7	19.7	51.0	8.2 (6.0)	(5.5 - 7.5)	1389	11	809
	60	215/60 R 16	95 H	SL	BSW	15574420000	No	26.2	21.6	51.0	8.7 (6.5)	(6.0 - 7.5)	1521	11	794
	60	225/60 R 16	98 H	SL	BSW	15574670000	No	26.6	23.5	51.0	9.0 (6.5)	(6.0 - 8.0)	1653	11	780
	65	205/65 R 16	95 H	SL	BSW	15574700000	No	26.5	22.5	51.0	8.2 (6.0)	(5.5 - 7.5)	1521	11	784
	65	215/65 R 16	98 H	SL	BSW	15574470000	No	27.0	22.3	51.0	8.7 (6.5)	(6.0 - 7.5)	1653	11	769
	65	225/65 R 16	100 H	SL	BSW	15574560000	No	27.5	24.7	51.0	9.0 (6.5)	(6.0 - 8.0)	1764	11	755
17	70	215/70 R 16	100 H	SL	BSW	15574660000	No	27.9	26.6	51.0	8.7 (6.5)	(5.5 - 7.0)	1764	11	746
	45	215/45 R 17	87 V	SL	BSW	15574460000	Yes	24.6	21.5	51.0	8.4 (7.0)	(7.0 - 8.0)	1201	11	844
	45	225/45 R 17	94 V	XL	BSW	15574500000	Yes	25.0	22.7	51.0	8.9 (7.5)	(7.0 - 8.5)	1477	11	832
	45	235/45 R 17	97 V	XL	BSW	15574890000	Yes	25.3	23.0	51.0	9.3 (8.0)	(7.5 - 9.0)	1609	11	820
	50	205/50 R 17	93 V	XL	BSW	15574730000	Yes	25.1	22.5	51.0	8.4 (6.5)	(5.5 - 7.5)	1433	11	829
	50	215/50 R 17	95 V	XL	BSW	15574600000	Yes	25.5	23.3	51.0	8.9 (7.0)	(6.0 - 7.5)	1521	11	816
	50	225/50 R 17	94 V	SL	BSW	15574550000	Yes	25.9	24.4	51.0	9.2 (7.0)	(6.0 - 8.0)	1477	11	803
	55	215/55 R 17	94 V	SL	BSW	15574440000	Yes	26.3	23.8	51.0	8.9 (7.0)	(6.0 - 7.5)	1477	11	790
	55	225/55 R 17	97 V	SL	BSW	15574720000	Yes	26.7	24.5	51.0	9.2 (7.0)	(6.0 - 8.0)	1609	11	777
	55	235/55 R 17	99 H	SL	BSW	15574530000	Yes	27.2	25.2	51.0	9.6 (7.5)	(6.5 - 8.5)	1709	11	764
	60	215/60 R 17	96 H	SL	BSW	15574740000	No	27.2	22.6	51.0	8.7 (6.5)	(6.0 - 7.5)	1565	11	765
	60	225/60 R 17	99 H	SL	BSW	15574520000	No	27.6	24.9	51.0	9.0 (6.5)	(6.0 - 8.0)	1709	11	752
	60	235/60 R 17	102 H	SL	BSW	15574780000	No	28.1	26.7	51.0	9.4 (7.0)	(6.5 - 8.5)	1874	11	739
	65	215/65 R 17	99 H	SL	BSW	15574860000	No	28.0	25.1	51.0	8.7 (6.5)	(6.0 - 7.5)	1709	11	742
65	225/65 R 17	102 H	SL	BSW	15574380000	No	28.5	27.1	51.0	9.0 (6.5)	(6.0 - 8.0)	1874	11	729	
65	235/65 R 17	104 H	SL	BSW	15574480000	No	29.0	28.8	51.0	9.4 (7.0)	(6.5 - 8.5)	1984	11	716	
18	40	225/40 R 18	92 V	XL	BSW	15574610000	Yes	25.1	22.7	51.0	9.1 (8.0)	(7.5 - 9.0)	1389	11	828
	40	245/40 R 18	97 V	XL	BSW	15574820000	Yes	25.7	22.8	51.0	9.8 (8.5)	(8.0 - 9.5)	1609	11	808
	45	225/45 R 18	95 V	XL	BSW	15574630000	Yes	26.0	23.1	51.0	8.9 (7.5)	(7.0 - 8.5)	1521	11	800
	45	235/45 R 18	98 V	XL	BSW	15574450000	Yes	26.3	24.4	51.0	9.3 (8.0)	(7.5 - 9.0)	1653	11	789
	45	245/45 R 18	100 V	XL	BSW	15574870000	Yes	26.7	23.8	51.0	9.6 (8.0)	(7.5 - 9.0)	1764	11	779
	50	225/50 R 18	95 H	SL	BSW	15574830000	Yes	26.9	23.4	51.0	9.2 (7.0)	(6.0 - 8.0)	1521	11	773
	50	235/50 R 18	97 V	SL	BSW	15574590000	Yes	27.3	25.1	51.0	9.6 (7.5)	(6.5 - 8.5)	1609	11	762
	55	225/55 R 18	98 H	SL	BSW	15574810000	Yes	27.7	26.5	51.0	9.2 (7.0)	(6.0 - 8.0)	1653	11	749
	55	235/55 R 18	100 V	SL	BSW	15574510000	Yes	28.2	26.7	51.0	9.6 (7.5)	(6.5 - 8.5)	1764	11	737
	55	245/55 R 18	103 V	SL	BSW	15574840000	Yes	28.6	27.5	51.0	10.0 (7.5)	(7.0 - 8.5)	1929	11	726

BSW = Black Sidewall



ALTIMAX™ 365 AW | Product Data

PASSENGER & CROSSOVER | ALL-WEATHER | TOURING

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ND S)	REVS PER MILE
18	55	255/55 R 18	109 V	XL	BSW	15574750000	Yes	29.0	30.1	51.0	10.4 (8.0)	(7.0 - 9.0)	2271	11	715
	60	225/60 R 18	100 H	SL	BSW	15574800000	No	28.6	26.7	51.0	9.0 (6.5)	(6.0 - 8.0)	1764	11	726
	60	235/60 R 18	107 H	XL	BSW	15574430000	No	29.1	28.3	51.0	9.4 (7.0)	(6.5 - 8.5)	2149	11	714
	60	245/60 R 18	105 H	SL	BSW	15574620000	No	29.6	31.3	51.0	9.8 (7.0)	(7.0 - 8.5)	2039	11	702
	65	235/65 R 18	106 H	SL	BSW	15574760000	No	30.0	30.1	51.0	9.4 (7.0)	(6.5 - 8.5)	2094	11	692
19	45	245/45 R 19	102 V	XL	BSW	15574880000	Yes	27.7	25.9	51.0	9.6 (8.0)	(7.5 - 9.0)	1874	11	750
	50	255/50 R 19	107 V	XL	BSW	15574900000	Yes	29.0	31.5	51.0	10.4 (8.0)	(7.0 - 9.0)	2149	11	715
	55	225/55 R 19	99 H	SL	BSW	15574650000	Yes	28.7	26.8	51.0	9.2 (7.0)	(6.0 - 8.0)	1709	11	723
	55	235/55 R 19	105 H	XL	BSW	15574680000	Yes	29.2	27.0	51.0	9.6 (7.5)	(6.5 - 8.5)	2039	11	712
	55	245/55 R 19	103 H	SL	BSW	15574710000	Yes	29.6	31.8	51.0	10.0 (7.5)	(7.0 - 8.5)	1929	11	702
20	50	245/50 R 20	105 V	XL	BSW	15574580000	Yes	29.6	27.7	51.0	10.0 (7.5)	(7.0 - 8.5)	2039	11	701
	55	235/55 R 20	102 V	SL	BSW	15574770000	Yes	30.2	29.4	51.0	9.6 (7.5)	(6.5 - 8.5)	1874	11	688

BSW = Black Sidewall

GENERAL TIRE  TM

DELIVERS



CROSSOVER & LT/SUV | ALL-SEASON | TOURING

GRABBER™ HTS⁶⁰

Rim Diameter



15" - 22"

Aspect Ratio



45 - 85
(& Width 10.50)

Tread Pattern



Symmetric

TREADWEAR	TRACTION	TEMPERATURE	SPEED	WARRANTY
680 (P Metric)	A	B	S & T	65,000 Miles
660 (P Metric)	A	A	H	50,000 Miles
-- (LT Metric)	--	--	S & R	50,000 Miles



DURAGEN
EG
TECHNOLOGY

- Enhances strength and durability
- Delivers cut-and-chip resistance
- Extends tread life

Sample Vehicle Fitments Include:

- Acura
- BMW
- Cadillac
- Chevrolet
- Dodge
- Ford
- Honda
- Hyundai
- Infinity: Pickup Trucks & SUVs
- Jeep
- Nissan

Benefits

- Reliable braking on wet roads
- Responsive handling on wet and dry roads
- Enhanced durability
- Low road noise
- Last-lasting treadwear



CUSTOMER SATISFACTION TRIAL

Or the first 2/32^{nds} of tread. See warranty manual for complete details.

GRABBER™ HTS60 | Product Data

CROSSOVER & LT/SUV | ALL-SEASON | TOURING

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32nds)	REVS PER MILE
15	10.50	31 X 10.50 R 15 LT	109 R	C	OWL	04505070000	Yes	31.0	44.6	50.0	10.6 (8.5)	(7.0 - 9.0)	2270	14	670
	70	255/70 R 15	108 S	SL	OWL	04504580000	Yes	29.1	33.8	44.0	10.2 (7.5)	(6.5 - 8.5)	2205	12	715
	75	265/75 R 15	112 S	SL	OWL	04504570000	Yes	30.6	36.4	44.0	10.5 (7.5)	(7.0 - 9.0)	2469	12	678
16	65	255/65 R 16	109 H	SL	BSW	04504740000	Yes	29.1	33.5	51.0	10.2 (7.5)	(7.0 - 9.0)	2271	12	715
	65	255/65 R 16	109 S	SL	OWL	04504730000	Yes	29.1	33.6	44.0	10.2 (7.5)	(7.0 - 9.0)	2271	12	715
	70	215/70 R 16	100 T	SL	OWL	04504640000	Yes	27.9	25.9	44.0	8.7 (6.5)	(5.5 - 7.0)	1764	12	746
	70	225/70 R 16	103 T	SL	OWL	04504650000	Yes	28.4	30.2	44.0	9.0 (6.5)	(6.0 - 7.5)	1929	12	731
	70	235/70 R 16	106 T	SL	BSW	04504660000	Yes	29.0	30.4	44.0	9.4 (7.0)	(6.0 - 8.0)	2094	12	718
	70	235/70 R 16	106 T	SL	OWL	04504670000	Yes	29.0	30.3	44.0	9.4 (7.0)	(6.0 - 8.0)	2094	12	718
	70	245/70 R 16	107 T	SL	BSW	04504680000	Yes	29.5	34.0	44.0	9.8 (7.0)	(6.5 - 8.0)	2149	12	704
	70	245/70 R 16	107 T	SL	OWL	04504690000	Yes	29.5	33.1	44.0	9.8 (7.0)	(6.5 - 8.0)	2149	12	704
	70	255/70 R 16	111 S	SL	OWL	04504700000	Yes	30.1	35.7	44.0	10.2 (7.5)	(6.5 - 8.5)	2403	12	691
	70	265/70 R 16	112 T	SL	BSW	04504710000	Yes	30.6	37.2	44.0	10.7 (8.0)	(7.0 - 9.0)	2469	12	679
	70	265/70 R 16	112 T	SL	OWL	04504720000	Yes	30.6	38.2	44.0	10.7 (8.0)	(7.0 - 9.0)	2469	12	679
	75	225/75 R 16	104 S	SL	OWL	04504590000	Yes	29.3	30.0	44.0	8.8 (6.0)	(6.0 - 7.5)	1984	12	709
	75	235/75 R 16	108 S	SL	OWL	04504600000	Yes	29.9	32.7	44.0	9.3 (6.5)	(6.0 - 8.0)	2205	12	695
	75	245/75 R 16	111 S	SL	BSW	04504610000	Yes	30.5	34.3	44.0	9.8 (7.0)	(6.5 - 8.0)	2403	12	682
	75	245/75 R 16	111 S	SL	OWL	04504620000	Yes	30.5	34.9	44.0	9.8 (7.0)	(6.5 - 8.0)	2403	12	682
	75	265/75 R 16	116 T	SL	OWL	04504630000	Yes	31.6	40.4	44.0	10.5 (7.5)	(7.0 - 9.0)	2756	12	656
	75	LT245/75 R 16	120/116 S	E	BSW	04505090000	Yes	30.5	44.3	80.0	9.8 (7.0)	(6.5 - 8.0)	3085	14	682
	75	LT245/75 R 16	120/116 S	E	OWL	04505100000	Yes	30.5	45.3	80.0	9.8 (7.0)	(6.5 - 8.0)	3085	14	682
	75	LT265/75 R 16	123/120 R	E	OWL	04505120000	Yes	31.6	49.7	80.0	10.5 (7.5)	(7.0 - 8.0)	3415	14	656
	85	LT235/85 R 16	120/116 R	E	OWL	04505080000	Yes	31.7	44.9	80.0	9.3 (6.5)	(6.0 - 7.5)	3085	14	655
17	60	275/60 R 17	110 T	SL	OWL	04504860000	Yes	30.0	37.8	44.0	11.0 (8.0)	(7.5 - 9.5)	2337	12	693
	65	235/65 R 17	108 H	XL	BSW	04504810000	Yes	29.0	30.6	51.0	9.4 (7.0)	(6.5 - 8.5)	2205	12	716
	65	235/65 R 17	108 T	XL	OWL	04504800000	Yes	29.0	31.3	51.0	9.4 (7.0)	(6.5 - 8.5)	2205	12	716
	65	245/65 R 17	107 T	SL	BSW	04504820000	Yes	29.5	34.3	44.0	9.8 (7.0)	(7.0 - 8.5)	2149	12	703
	65	245/65 R 17	107 T	SL	OWL	04504830000	Yes	29.5	35.0	44.0	9.8 (7.0)	(7.0 - 8.5)	2149	12	703
	65	255/65 R 17	110 T	SL	OWL	04504840000	Yes	30.1	38.4	44.0	10.2 (7.5)	(7.0 - 9.0)	2337	12	691
	65	265/65 R 17	112 T	SL	OWL	04504850000	Yes	30.6	39.0	44.0	10.7 (8.0)	(7.5 - 9.5)	2469	12	680
	70	235/70 R 17	111 T	XL	OWL	04504760000	Yes	30.0	33.5	51.0	9.4 (7.0)	(6.0 - 8.0)	2403	12	694
	70	245/70 R 17	110 T	SL	OWL	04504770000	Yes	30.5	35.9	44.0	9.8 (7.0)	(6.5 - 8.0)	2337	12	681
	70	265/70 R 17	115 S	SL	BSW	04504780000	Yes	31.6	40.3	44.0	10.7 (8.0)	(7.0 - 9.0)	2679	12	657
	70	265/70 R 17	115 S	SL	OWL	04504790000	Yes	31.6	40.8	44.0	10.7 (8.0)	(7.0 - 9.0)	2679	12	657
	70	LT245/70 R 17	119/116 S	E	OWL	04505160000	Yes	30.5	44.8	80.0	9.8 (7.0)	(6.5 - 8.0)	3000	14	681
	70	LT265/70 R 17	121/118 S	E	OWL	04505170000	Yes	31.6	51.1	80.0	10.7 (8.0)	(7.0 - 8.5)	3195	14	657
	75	LT245/75 R 17	121/118 S	E	BSW	04505140000	Yes	31.5	46.5	80.0	9.8 (7.0)	(6.5 - 7.5)	3195	14	660
	75	LT245/75 R 17	121/118 S	E	OWL	04505150000	Yes	31.5	47.5	80.0	9.8 (7.0)	(6.5 - 7.5)	3195	14	660
	80	LT235/80 R 17	120/117 R	E	OWL	04505130000	Yes	31.8	47.2	80.0	9.3 (6.5)	(6.0 - 7.5)	3085	14	653
	18	55	255/55 R 18	109 H	XL	BSW	04504960000	Yes	29.0	35.8	51.0	10.4 (8.0)	(7.0 - 9.0)	2271	12

BSW = Black Sidewall | OWL = Outlined White Letter



GRABBER™ HTS⁶⁰ | Product Data

CROSSOVER & LT/SUV | ALL-SEASON | TOURING

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ND S)	REVS PER MILE
18	60	235/60 R 18	103 H	SL	BSW	04504930000	Yes	29.1	31.7	51.0	9.4 (7.0)	(6.5 - 8.5)	1929	12	714
	60	245/60 R 18	105 H	SL	BSW	04504940000	Yes	29.6	32.0	51.0	9.8 (7.0)	(7.0 - 8.5)	2039	12	702
	60	265/60 R 18	110 T	SL	OWL	04504950000	Yes	30.5	39.2	44.0	10.7 (8.0)	(7.5 - 9.5)	2337	12	681
	65	235/65 R 18	106 T	SL	OWL	04504890000	Yes	30.0	32.4	44.0	9.4 (7.0)	(6.5 - 8.5)	2094	12	692
	65	255/65 R 18	111 S	SL	BSW	04504900000	Yes	31.1	38.3	44.0	10.2 (7.5)	(7.0 - 9.0)	2403	12	669
	65	265/65 R 18	114 T	SL	OWL	04504910000	Yes	31.6	38.3	44.0	10.7 (8.0)	(7.5 - 9.5)	2601	12	658
	65	275/65 R 18	116 T	SL	OWL	04504920000	Yes	32.1	40.7	44.0	11.0 (8.0)	(7.5 - 9.5)	2756	12	648
	65	LT275/65 R 18	123/120 S	E	OWL	04505190000	Yes	32.1	52.7	80.0	11.0 (8.0)	(7.5 - 9.0)	3415	14	648
	70	255/70 R 18	113 T	SL	OWL	04504870000	Yes	32.1	40.0	44.0	10.2 (7.5)	(6.5 - 8.5)	2535	12	648
	70	265/70 R 18	116 T	SL	OWL	04504880000	Yes	32.6	40.9	44.0	10.7 (8.0)	(7.0 - 9.0)	2756	12	637
70	LT275/70 R 18	125/122 S	E	OWL	04505180000	Yes	33.2	55.2	80.0	11.0 (8.0)	(7.0 - 8.5)	3640	14	627	
19	50	255/50 R 19	107 H	XL	BSW	04509210000	Yes	29.0	35.1	51.0	10.4 (8.0)	(7.0 - 9.0)	2149	12	715
	55	235/55 R 19	101 H	SL	BSW	04504990000	Yes	29.2	30.2	51.0	9.6 (7.5)	(6.5 - 8.5)	1819	12	712
	55	245/55 R 19	103 T	SL	BSW	04505000000	Yes	29.6	31.9	44.0	10.0 (7.5)	(7.0 - 8.5)	1929	12	702
	60	255/60 R 19	109 H	SL	BSW	04504980000	Yes	31.0	38.8	51.0	10.2 (7.5)	(7.0 - 9.0)	2271	12	669
	60	255/60 R 19	109 S	SL	BSW	04504970000	Yes	31.0	38.8	44.0	10.2 (7.5)	(7.0 - 9.0)	2271	12	669
20	50	245/50 R 20	102 H	SL	BSW	04505040000	Yes	29.6	32.2	51.0	10.0 (7.5)	(7.0 - 8.5)	1874	12	701
	50	255/50 R 20	109 H	XL	BSW	04509240000	Yes	30.0	35.8	51.0	10.4 (8.0)	(7.0 - 9.0)	2271	12	692
	50	265/50 R 20	107 T	SL	BSW	04505050000	Yes	30.4	37.7	44.0	10.9 (8.5)	(7.5 - 9.5)	2149	12	683
	55	235/55 R 20	102 H	SL	BSW	04509220000	Yes	30.2	29.9	51.0	9.6 (7.5)	(6.5 - 8.5)	1874	12	688
	55	255/55 R 20	107 H	SL	BSW	04505200000	Yes	31.0	36.8	51.0	10.4 (8.0)	(7.0 - 9.0)	2149	12	669
	55	275/55 R 20	117 H	XL	BSW	04505030000	Yes	31.9	39.3	51.0	11.2 (8.5)	(7.5 - 9.5)	2833	12	651
	55	275/55 R 20	117 T	XL	BSW	04505020000	Yes	31.9	39.3	51.0	11.2 (8.5)	(7.5 - 9.5)	2833	12	651
	60	245/60 R 20	107 H	SL	BSW	04509230000	Yes	31.6	34.4	51.0	9.8 (7.0)	(7.0 - 8.5)	2149	12	658
	60	275/60 R 20	115 S	SL	BSW	04505640000	No	33.0	40.6	44.0	11.0 (8.0)	(7.5 - 9.5)	2679	11	630
	60	275/60 R 20	115 S	SL	BSW	04505270000	No	33.0	36.4	44.0	11.0 (8.0)	(7.5 - 9.5)	2679	11	630
	60	275/60 R 20	116 T	XL	BSW	04509800000	No	33.0	34.3	51.0	11 (8)	(7.5 - 9.5)	2756	10	630
22	65	LT275/65 R 20	126/123 S	E	OWL	04509250000	Yes	34.1	54.1	80.0	11.0 (8.0)	(7.5 - 9.5)	3750	14	610
	45	285/45 R 22	114 H	XL	BSW	04491490000	Yes	32.1	38.0	51.0	11.2 (9.5)	(9.0 - 10.5)	2601	10	647
	50	275/50 R 22	115 T	XL	BSW	04490900000	Yes	32.8	39.1	51.0	11.2 (8.5)	(7.5 - 9.5)	2679	10	633

BSW = Black Sidewall | OWL = Outlined White Letter

GENERAL TIRE  TM

DELIVERS



DELIVERS

for treading on or off the beaten path.

Our **all-terrain** products strike the balance between robust off-road durability and exceptional on-road performance.



Grabber™ APT



Grabber™ A/T^X



Grabber™ X³





CROSSOVER & LT/SUV | ALL-SEASON | ALL-TERRAIN

GRABBER™ APT

Rim Diameter



16" - 22"

Aspect Ratio



45 - 85

Tread Pattern



Symmetric

TREADWEAR	TRACTION	TEMPERATURE	SPEED	WARRANTY
520 (P Metric)	A	B	R, S, T & H	60,000 Miles
-- (LT Metric)	--	--	R, S, T & H	60,000 Miles


Benefits

- Available in commercial LT-metric sizes
- Balanced on-road performance with off-road traction
- Enhanced strength & durability
- Low road noise
- Long-lasting treadwear



DURAGEN
EG
TECHNOLOGY

- Enhances strength and durability
- Delivers cut-and-chip resistance
- Extends tread life



3-Peak Mountain Snowflake
Select sizes meet the severe snow service requirements of the U.S. Tire Manufacturers Association (USTMA) and the Tire and Rubber Association of Canada (TRAC).

Sample Vehicle Fitments Include:

- Chevrolet: Silverado, Tahoe & Suburban
- Ford: F-150, Explorer, Escape & Super Duty
- GMA: Sierra & Yukon
- Jeep: Grand Cherokee & Wrangler
- Nissan: Frontier, Rogue & Pathfinder
- Ram: Pickup Trucks



CUSTOMER SATISFACTION TRIAL

Or the first 2/32^{nds} of tread. See warranty manual for complete details.

GRABBER™ APT | Product Data

CROSSOVER & LT/SUV | ALL-SEASON | ALL-TERRAIN

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ^{nds})	REVS PER MILE
16	65	235/65 R 16 C	121/119 R	E	BSW	04504170000	Yes	28.0	37.2	90.0	9.4 (7)	(6.5 - 7.5)	3195	15	741
	70	235/70 R 16	106 T	SL	OWL	04507900000	Yes	29.0	34.9	44.0	9.4 (7.0)	(6.0 - 8.0)	2094	14	718
	70	255/70 R 16	111 T	SL	OWL	04507920000	Yes	30.1	39.7	44.0	10.2 (7.5)	(6.5 - 8.5)	2403	14	691
	70	265/70 R 16	112 T	SL	OWL	04507930000	Yes	30.6	41.6	44.0	10.7 (8.0)	(7.0 - 9.0)	2469	14	679
	75	245/75 R 16	111 T	SL	OWL	04507810000	Yes	30.5	36.7	44.0	9.8 (7.0)	(6.5 - 8.0)	2403	14	682
	75	265/75 R 16	116 T	SL	OWL	04507870000	Yes	31.6	42.1	44.0	10.5 (7.5)	(7.0 - 9.0)	2756	14	656
	75	LT225/75 R 16	115/112 R	E	BSW	04504190000	Yes	29.3	43.8	80.0	8.8 (6.0)	(6.0 - 7.0)	2680	16	709
	75	LT245/75 R 16	120/116 S	E	BSW	04504180000	Yes	30.5	47.7	80.0	9.8 (7.0)	(6.5 - 8.0)	3085	16	682
	75	LT265/75 R 16	123/120 R	E	BSW	04504350000	Yes	31.6	50.4	80.0	10.5 (7.5)	(7.0 - 8.0)	3415	16	656
	85	LT215/85 R 16	115/112 R	E	BSW	04504270000	Yes	30.4	43.6	80.0	8.5 (6.0)	(5.5 - 7.0)	2680	16	684
85	LT235/85 R 16	120/116 R	E	BSW	04504280000	Yes	31.7	47.3	80.0	9.3 (6.5)	(6.0 - 7.5)	3085	16	655	
17	65	245/65 R 17	107 T	SL	OWL	04508000000	Yes	29.5	34.9	44.0	9.8 (7.0)	(7.0 - 8.5)	2149	14	703
	65	255/65 R 17	110 T	SL	OWL	04508010000	Yes	30.1	38.3	44.0	10.2 (7.5)	(7.0 - 9.0)	2337	14	691
	65	265/65 R 17	112 T	SL	OWL	04508020000	Yes	30.6	39.6	44.0	10.7 (8.0)	(7.5 - 9.5)	2469	14	680
	70	245/70 R 17	110 T	SL	OWL	04507960000	Yes	30.5	39.3	44.0	9.8 (7.0)	(6.5 - 8.0)	2337	14	681
	70	255/70 R 17	112 T	SL	OWL	04507970000	Yes	31.1	39.9	44.0	10.2 (7.5)	(6.5 - 8.5)	2469	14	669
	70	265/70 R 17	115 T	SL	OWL	04507980000	Yes	31.6	44.4	44.0	10.7 (8.0)	(7.0 - 9.0)	2679	14	657
	70	LT245/70 R 17	119/116 R	E	OWL	04504410000	Yes	30.5	47.6	80.0	9.8 (7.0)	(6.5 - 8.0)	3000	16	681
	70	LT265/70 R 17	112/109 S	C	BSW	15570730000	Yes	31.6	42.8	50.0	10.7 (8.0)	(7.0 - 8.5)	2470	12	657
	70	P285/70 R 17	117 T	SL	OWL	04507990000	Yes	32.7	46.8	44.0	11.5 (8.5)	(7.5 - 9.5)	2833	14	635
	75	235/75 R 17	109 T	SL	OWL	04507940000	Yes	30.9	38.6	44.0	9.3 (6.5)	(6.0 - 8.0)	2271	14	673
	75	255/75 R 17	115 T	SL	OWL	04507950000	Yes	32.1	41.2	44.0	10.0 (7.0)	(6.5 - 8.5)	2679	14	648
	75	LT245/75 R 17	121/118 S	E	BSW	04504310000	Yes	31.5	50.0	80.0	9.8 (7.0)	(6.5 - 7.5)	3195	16	660
80	LT235/80 R 17	120/117 R	E	BSW	04504250000	Yes	31.8	48.5	80.0	9.3 (6.5)	(6.0 - 7.5)	3085	16	653	
18	60	265/60 R 18	110 T	SL	BSW	04508080000	Yes	30.5	39.7	44.0	10.7 (8.0)	(7.5 - 9.5)	2337	14	681
	65	265/65 R 18	114 T	SL	OWL	04508060000	Yes	31.6	41.7	44.0	10.7 (8.0)	(7.5 - 9.5)	2601	14	658
	65	275/65 R 18	116 T	SL	OWL	04508070000	Yes	32.1	44.8	44.0	11.0 (8.0)	(7.5 - 9.5)	2756	14	648
	65	LT275/65 R 18	123/120 R	E	BSW	04507640000	Yes	32.1	55.9	80.0	11.0 (8.0)	(7.5 - 9.0)	3415	15	648
	70	255/70 R 18	113 T	SL	OWL	04508030000	Yes	32.1	41.7	44.0	10.2 (7.5)	(6.5 - 8.5)	2535	14	648
	70	265/70 R 18	116 T	SL	OWL	04508040000	Yes	32.6	45.5	44.0	10.7 (8.0)	(7.0 - 9.0)	2756	14	637
	70	LT 265/70 R 18	113/110 S	C	BSW	04492580000	Yes	32.6	43.9	50.0	10.7 (8.0)	(7.0 - 9.0)	2535	13	637
	70	P 275/70 R 18	116 S	SL	BSW	04492870000	No	33.2	40.3	44.0	11.0 (8.0)	(7.0 - 9.0)	2756	13	627
	70	LT265/70 R 18	113/110 S	C	OWL	04509860000	Yes	32.6	44.9	50.0	10.7 (8.0)	(7.0 - 9.0)	2535	12	637
	70	LT275/70 R 18	125/122 S	E	OWL	04508050000	Yes	33.2	56.7	80.0	11.0 (8.0)	(7.0 - 8.5)	3640	16	627
70	P275/70 R 18	116 S	SL	OWL	04503130000	No	33.2	43.7	44.0	11.0 (8.0)	(7.0 - 9.0)	2756	12	627	
20	55	275/55 R 20	117 T	XL	BSW	04508100000	Yes	31.9	44.4	51.0	11.2 (8.5)	(7.5 - 9.5)	2833	14	651
	60	275/60 R 20	115 T	SL	BSW	04508090000	Yes	33.0	45.0	44.0	11.0 (8.0)	(7.5 - 9.5)	2679	14	630
	65	LT 275/65 R 20	126/123 S	E	BSW	04492610000	Yes	34.1	56.8	80.0	11.0 (8.0)	(7.5 - 9.5)	3750	16	610
22	45	285/45 R 22	114 H	XL	BSW	04508110000	Yes	32.1	43.0	51.0	11.2 (9.5)	(9.0 - 10.5)	2601	13	647

BSW = Black Sidewall | OWL = Outlined White Letter





LT/SUV | ALL-SEASON | ALL-TERRAIN

GRABBER™ A/TX

Rim Diameter



14" - 20"

Aspect Ratio



50 - 85
(& Widths 8.50 - 13.50)

Tread Pattern



Symmetric

TREADWEAR	TRACTION	TEMPERATURE	SPEED	WARRANTY
640 (P Metric)	A	B	Q, R, S & T	60,000 Miles
-- (LT Metric)	--	--	Q, R, S & T	50,000 Miles

Benefits

- Balanced off-road traction with on-road performance
- Robust strength and durability
- Aggressive styling
- Low road noise
- Long-lasting treadwear



DURAGEN
EGG
TECHNOLOGY

- Enhances strength and durability
- Delivers cut-and-chip resistance
- Extends tread life



3-Peak Mountain Snowflake

Meets the severe snow service requirements of the U.S. Tire Manufacturers Association (USTMA) and the Tire and Rubber Association of Canada (TRAC).



Pinned for Winter Studs

Stud length for metric sizes: 12mm (TSMI #13). Stud size listed on the tire's sidewall.

Sample Vehicle Fitsments Include:

- Chevrolet: Silverado, Tahoe & Suburban
- Ford: F-150, Explorer, Escape & Super Duty
- GMA: Sierra & Yukon
- Jeep: Grand Cherokee & Wrangler
- Nissan: Frontier, Rogue & Pathfinder
- Ram: Pickup Trucks



CUSTOMER SATISFACTION TRIAL

Or the first 2/32^{nds} of tread. See warranty manual for complete details.

GRABBER™ A/T^X | Product Data

LT/SUV | ALL-SEASON | ALL-TERRAIN

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ^{nds})	REVS PER MILE	
14	8.50	27 X 8.50 R 14 LT	95 Q	C	RWL	04508120000	Yes	27.0	30.9	50.0	8.6 (7.0)	(6.0 - 7.5)	1520	16	769	
	9.50	30 X 9.50 R 15 LT	104 S	C	RWL	04508400000	Yes	30.0	38.5	50.0	9.4 (7.5)	(6.5 - 8.5)	1984	16	692	
	10.50	31 X 10.50 R 15 LT	109 S	C	RWL	04505590000	Yes	31.0	45.7	50.0	10.6 (8.5)	(7.0 - 9.0)	2270	17	670	
	12.50	33 X 12.50 R 15 LT	108 R	C	RWL	04505630000	Yes	33.0	59.1	36.0	12.5 (10.0)	(8.5 - 11.0)	2205	16	630	
	12.50	35 X 12.50 R 15 LT	113 Q	C	RWL	04507050000	Yes	35.0	64.1	35.0	12.5 (10.0)	(8.5 - 11.0)	2535	16	594	
	15	70	225/70 R 15	100 T	SL	RWL	04504110000	Yes	27.4	31.3	44.0	9.0 (6.5)	(6.0 - 7.5)	1764	14	758
		70	255/70 R 15	108 T	SL	BSW	04503960000	Yes	29.1	36.8	44.0	10.2 (7.5)	(6.5 - 8.5)	2205	14	715
		70	265/70 R 15	112 T	SL	RWL	04504080000	Yes	29.6	38.6	44.0	10.7 (8.0)	(7.0 - 9.0)	2469	14	702
		75	205/75 R 15	97 T	SL	RWL	04503590000	Yes	27.1	28.5	44.0	8.0 (5.5)	(5.0 - 7.0)	1609	14	766
		75	215/75 R 15	100 T	SL	RWL	04503850000	Yes	27.7	31.5	44.0	8.5 (6.0)	(5.5 - 7.0)	1764	14	750
75	LT235/75 R 15	104/101 S	C	RWL	04507270000	Yes	28.9	36.6	50.0	9.3 (6.5)	(6.0 - 7.0)	1985	17	719		
16	65	215/65 R 16	98 T	SL	BSW	04503600000	Yes	27.0	29.7	44.0	8.7 (6.5)	(6.0 - 7.5)	1653	14	769	
	70	215/70 R 16	100 T	SL	RWL	04503610000	Yes	27.9	31.0	44.0	8.7 (6.5)	(5.5 - 7.0)	1764	14	746	
	70	235/70 R 16	106 T	SL	RWL	04503890000	Yes	29.0	36.2	44.0	9.4 (7.0)	(6.0 - 8.0)	2094	14	718	
	70	255/70 R 16	111 T	SL	RWL	04504000000	Yes	30.1	39.7	44.0	10.2 (7.5)	(6.5 - 8.5)	2403	14	691	
	70	265/70 R 16	112 T	SL	RWL	04509710000	Yes	30.6	41.3	44.0	10.7 (8.0)	(7.0 - 9.0)	2469	14	679	
	70	LT305/70 R 16	124/121 R	E	RWL	04506790000	Yes	32.8	62.6	65.0	12.2 (9.0)	(8.0 - 9.5)	3525	16	633	
	75	225/75 R 16	108 T	XL	RWL	04503140000	Yes	29.3	32.4	51.0	8.8 (6.0)	(6.0 - 7.5)	2205	14	709	
	75	LT245/75 R 16	120/116 R	E	RWL	04508460000	Yes	30.5	48.1	80.0	9.8 (7.0)	(6.5 - 8.0)	3086	16	682	
	75	LT265/75 R 16	123/120 R	E	RWL	04506330000	Yes	31.6	52.4	80.0	10.5 (7.5)	(7.0 - 8.0)	3415	16	656	
	75	LT285/75 R 16	126/123 R	E	RWL	04508480000	Yes	32.8	58.3	80.0	11.3 (8.0)	(7.5 - 9.0)	3750	16	633	
	75	LT315/75 R 16	127/124 R	E	RWL	04508490000	Yes	34.6	64.6	65.0	12.3 (8.5)	(8.0 - 11.0)	3860	16	600	
85	LT235/85 R 16	120/116 S	E	RWL	04508440000	Yes	31.7	49.5	80.0	9.3 (6.5)	(6.0 - 7.5)	3085	16	655		
17	12.50	35 X 12.50 R 17 LT	121 R	E	RWL	04507150000	Yes	35.0	62.9	65.0	12.5 (10.0)	(8.5 - 11.0)	3195	16	594	
	12.50	37 X 12.50 R 17 LT	124 R	D	RWL	04505340000	Yes	37.0	72.2	50.0	12.5 (10.0)	(8.5 - 11.0)	3525	16	561	
	65	265/65 R 17	112 T	SL	RWL	04509760000	Yes	30.6	43.2	44.0	10.7 (8.0)	(7.5 - 9.5)	2469	14	680	
	70	245/70 R 17	110 T	SL	RWL	04509740000	Yes	30.5	40.5	44.0	9.8 (7.0)	(6.5 - 8.0)	2337	14	681	
	70	255/70 R 17	112 T	SL	RWL	04509750000	Yes	31.1	42.1	44.0	10.2 (7.5)	(6.5 - 8.5)	2469	14	669	
	70	265/70 R 17	115 T	SL	RWL	04507630000	Yes	31.6	44.4	44.0	10.7 (8.0)	(7.0 - 9.0)	2679	14	657	
	70	LT245/70 R 17	119/116 S	E	RWL	04508530000	Yes	30.5	47.7	80.0	9.8 (7.0)	(6.5 - 8.0)	3000	16	681	
	70	LT265/70 R 17	112/109 T	C	BSW	04509790000	Yes	31.6	46.9	50.0	10.7 (8.0)	(7.0 - 8.5)	2470	16	657	
	70	LT265/70 R 17	121/118 S	E	RWL	04505740000	Yes	31.6	53.0	80.0	10.7 (8.0)	(7.0 - 8.5)	3195	16	657	
	70	LT275/70 R 17	121/118 R	E	RWL	04508360000	Yes	32.2	56.7	80.0	11.0 (8.0)	(7.0 - 8.5)	3195	16	646	
	70	LT285/70 R 17	121/118 S	E	RWL	04507250000	Yes	32.7	58.0	80.0	11.5 (8.5)	(7.5 - 9.0)	3195	16	635	
	70	LT315/70 R 17	121/118 S	E	RWL	04508340000	Yes	34.4	65.7	65.0	12.7 (9.5)	(8.0 - 11.0)	3195	16	605	
	75	LT245/75 R 17	121/118 S	E	RWL	04509880000	Yes	31.5	50.5	80.0	9.8 (7.0)	(6.5 - 7.5)	3195	16	660	
	80	LT235/80 R 17	120/117 R	E	BSW	04508510000	Yes	31.8	49.5	80.0	9.3 (6.5)	(6.0 - 7.5)	3086	16	653	
18	12.50	35 X 12.50 R 18 LT	123 R	E	RWL	04505650000	Yes	35.0	65.6	65.0	12.5 (10.0)	(8.5 - 11.0)	3415	16	594	
	60	LT285/60 R 18	122/119 S	E	BSW	04508250000	Yes	31.5	54.7	80.0	11.5 (8.5)	(8.0 - 10.0)	3305	16	660	
	65	275/65 R 18	116 T	SL	RWL	04509720000	Yes	32.1	45.2	44.0	11.0 (8.0)	(7.5 - 9.5)	2756	14	648	

BSW = Black Sidewall | RWL = Raised White Letter



GRABBER™ A/T^X | Product Data

LT/SUV | ALL-SEASON | ALL-TERRAIN

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ND S)	REVS PER MILE
18	65	LT275/65 R 18	123/120 R	E	RWL	04506340000	Yes	32.1	56.4	80.0	11.0 (8.0)	(7.5 - 9.0)	3415	16	648
	65	LT285/65 R 18	125/122 S	E	RWL	04508270000	Yes	32.6	57.0	80.0	11.5 (8.5)	(8.0 - 10.0)	3640	16	637
	70	265/70 R 18	116 T	SL	RWL	04504090000	Yes	32.6	45.8	44.0	10.7 (8.0)	(7.0 - 9.0)	2756	14	637
	70	275/70 R 18	116 S	SL	BSW	04509780000	Yes	33.2	46.7	44.0	11.0 (8.0)	(7.0 - 9.0)	2756	14	627
	70	275/70 R 18	116 S	SL	BSW	04492430000	Yes	33.2	45.5	44.0	11.0 (8.0)	(7.0 - 9.0)	2756	14	627
	70	LT265/70 R 18	124/121 S	E	RWL	04506020000	Yes	32.6	55.1	80.0	10.7 (8.0)	(7.0 - 9.0)	3525	16	637
	70	LT275/70 R 18	125/122 R	E	RWL	04506780000	Yes	33.2	59.2	80.0	11.0 (8.0)	(7.0 - 8.5)	3640	16	627
20	12.50	33 X 12.50 R 20 LT	114 S	E	BSW	04508130000	Yes	33.0	64.3	65.0	12.5 (10.0)	(8.5 - 11.0)	2600	16	630
	12.50	35 X 12.50 R 20 LT	121 R	E	BSW	04505690000	Yes	35.0	71.2	65.0	12.5 (10.0)	(8.5 - 11.0)	3195	16	594
	13.50	37 X 13.50 R 20 LT	127 R	E	BSW	15571240000	Yes	37.0	76.2	65.0	13.6 (11.0)	(8.5 - 11.0)	3860	16	561
	50	305/50 R 20	120 T	XL	BSW	04508150000	Yes	32.0	48.9	51.0	12.4 (9.5)	(8.5 - 11.0)	3086	14	649
	55	275/55 R 20	113 T	SL	BSW	04509770000	Yes	31.9	45.4	44.0	11.2 (8.5)	(7.5 - 9.5)	2535	14	651
	55	LT275/55 R 20	115/112 T	D	BSW	04508180000	Yes	31.9	55.1	65.0	11.2 (8.5)	(7.5 - 9.5)	2680	15	651
	55	LT285/55 R 20	117/114 T	D	BSW	04508170000	Yes	32.3	61.2	65.0	11.7 (9.0)	(8.0 - 10.0)	2833	15	642
	55	LT305/55 R 20	121/118 S	E	BSW	04508160000	Yes	33.2	59.7	65.0	12.4 (9.5)	(8.5 - 11.0)	3195	16	626
	60	LT265/60 R 20	121/118 S	E	BSW	04508220000	Yes	32.5	57.4	80.0	10.7 (8.0)	(7.5 - 9.5)	3195	16	639
	60	LT275/60 R 20	119/116 S	D	BSW	04508210000	Yes	33.0	56.4	65.0	11.0 (8.0)	(7.5 - 9.5)	2998	16	630
	60	LT285/60 R 20	125/122 S	E	BSW	04508200000	Yes	33.5	60.7	80.0	11.5 (8.5)	(8.0 - 10.0)	3640	16	621
	60	LT325/60 R 20	126 S	E	BSW	04508190000	Yes	35.4	70.8	65.0	13.0 (9.5)	(9.0 - 12.0)	3750	16	588
	65	LT275/65 R 20	126/123 S	E	BSW	04508230000	Yes	34.1	58.5	80.0	11.0 (8.0)	(7.5 - 9.5)	3750	16	610
22	45	305/45 R 22	118 T	XL	BSW	04491710000	Yes	32.8	46.5	51.0	11.9 (10.0)	(9.5 - 11.5)	2910	14	633

BSW = Black Sidewall | RWL = Raised White Letter

GENERAL TIRE  TM

DELIVERS



LT/SUV | ALL-SEASON | MUD-TERRAIN

GRABBER™ X³

Rim Diameter



15" - 22"

Aspect Ratio



55 - 75
(& Widths 10.50 - 13.50)

Tread Pattern



Symmetric

TREADWEAR	TRACTION	TEMPERATURE	SPEED
--	--	--	Q

Benefits

- Aggressive, bold styling
- Low road noise
- Race-proven durability and performance
- Extreme off-road traction in mud, dirt & rock-covered terrain
- Impressive wet and winter performance



DURAGEN
EG
TECHNOLOGY

- Enhances strength and durability
- Delivers cut-and-chip resistance
- Extends tread life

Sample Vehicle Fitments Include:

- Chevrolet Suburban
- Ford Expedition
- GMC Hummer
- Jeep
- Toyota FJ Cruiser
- Various Pickup Trucks



CUSTOMER SATISFACTION TRIAL

Or the first 2/32^{nds} of tread. See warranty manual for complete details.

GRABBER™ X³ | Product Data

LT/SUV | ALL-SEASON | MUD-TERRAIN

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ND S)	REVS PER MILE
15	10.50	31 X 10.50 R 15 LT	109 Q	C	BSW	04505660000	Yes	31.0	54.2	50.0	10.6 (8.5)	(7.0 - 9.0)	2271	19	670
	10.50	33 X 10.50 R 15 LT	114 Q	C	SRL	04506840000	Yes	33.0	60.8	50.0	10.6 (8.5)	(7.0 - 9.0)	2601	21	630
	12.50	33 X 12.50 R 15 LT	108 Q	C	BSW	04505670000	Yes	33.0	67.2	35.0	12.5 (10.0)	(8.5 - 11.0)	2205	21	630
	12.50	35 X 12.50 R 15 LT	113 Q	C	BSW	04505680000	Yes	35.0	75.6	35.0	12.5 (10.0)	(8.5 - 11.0)	2535	21	594
16	75	LT265/75 R 16	112/109 Q	C	SRL	04505700000	Yes	31.6	50.9	50.0	10.5 (7.5)	(7.0 - 8.0)	2469	18	656
	75	LT265/75 R 16	123/120 Q	E	BSW	04505710000	Yes	31.6	57.6	80.0	10.5 (7.5)	(7.0 - 8.0)	3415	18	656
	75	LT285/75 R 16	126/123 Q	E	BSW	04505720000	Yes	32.8	63.3	80.0	11.3 (8.0)	(7.5 - 9.0)	3750	18	633
	75	LT315/75 R 16	127/124 Q	E	BSW	04505730000	Yes	34.6	74.4	65.0	12.3 (8.5)	(8.0 - 11.0)	3860	19	600
17	12.50	33 X 12.50 R 17 LT	114 Q	D	SRL	04505820000	Yes	33.0	70.7	50.0	12.5 (10.0)	(8.5 - 11.0)	2600	21	630
	12.50	33 X 12.50 R 17 LT	114 Q	D	BSW	04505830000	Yes	33.0	70.7	50.0	12.5 (10.0)	(8.5 - 11.0)	2600	21	630
	12.50	35 X 12.50 R 17 LT	111 Q	C	SRL	04509890000	Yes	35.0	70.5	35.0	12.5 (10.0)	(8.5 - 11.0)	2405	21	594
	12.50	35 X 12.50 R 17 LT	121 Q	E	SRL	04505840000	Yes	35.0	75.8	65.0	12.5 (10.0)	(8.5 - 11.0)	3195	21	594
	12.50	35 X 12.50 R 17 LT	121 Q	E	BSW	04505850000	Yes	35.0	75.8	65.0	12.5 (10.0)	(8.5 - 11.0)	3195	21	594
	12.50	37 X 12.50 R 17 LT	124 Q	D	SRL	04505860000	Yes	37.0	80.0	50.0	12.5 (10.0)	(8.5 - 11.0)	3525	21	561
	12.50	37 X 12.50 R 17 LT	124 Q	D	BSW	04505870000	Yes	37.0	80.1	50.0	12.5 (10.0)	(8.5 - 11.0)	3525	21	561
	70	LT265/70 R 17	121/118 Q	E	SRL	04505760000	Yes	31.6	59.2	80.0	10.7 (8.0)	(7.0 - 8.5)	3195	18	657
	70	LT265/70 R 17	121/118 Q	E	BSW	04505770000	Yes	31.6	59.2	80.0	10.7 (8.0)	(7.0 - 8.5)	3195	18	657
	70	LT285/70 R 17	121/118 Q	E	SRL	04505780000	Yes	32.7	64.8	80.0	11.5 (8.5)	(7.5 - 9.0)	3195	18	635
	70	LT295/70 R 17	121/118 Q	E	SRL	04505790000	Yes	33.3	67.5	80.0	11.8 (8.5)	(7.5 - 10.0)	3195	18	625
	70	LT295/70 R 17	121/118 Q	E	BSW	04505800000	Yes	33.3	67.5	80.0	11.8 (8.5)	(7.5 - 10.0)	3195	18	625
	70	LT315/70 R 17	121/118 Q	E	BSW	04505810000	Yes	34.4	73.0	65.0	12.7 (9.5)	(8.0 - 11.0)	3195	19	605
75	LT255/75 R 17	111/108 Q	C	BSW	04505750000	Yes	32.1	57.0	50.0	10.0 (7.0)	(6.5 - 8.5)	2405	18	648	
18	12.50	33 X 12.50 R 18 LT	118 Q	E	SRL	04505930000	Yes	33.0	72.5	65.0	12.5 (10.0)	(8.5 - 11.0)	2910	21	630
	12.50	33 X 12.50 R 18 LT	118 Q	E	BSW	04505940000	Yes	33.0	72.5	65.0	12.5 (10.0)	(8.5 - 11.0)	2910	21	630
	12.50	35 X 12.50 R 18 LT	123 Q	E	SRL	04505950000	Yes	35.0	74.8	65.0	12.5 (10.0)	(8.5 - 11.0)	3415	21	594
	12.50	35 X 12.50 R 18 LT	123 Q	E	BSW	04505960000	Yes	35.0	74.8	65.0	12.5 (10.0)	(8.5 - 11.0)	3415	21	594
	12.50	37 X 12.50 R 18 LT	128 Q	E	SRL	04505970000	Yes	37.0	78.6	65.0	12.5 (10.0)	(8.5 - 11.0)	3970	21	561
	60	LT265/60 R 18	119/116 Q	E	BSW	04509820000	Yes	30.5	55.0	80.0	10.7 (8.0)	(7.5 - 9.5)	3000	18	681
	65	LT275/65 R 18	123/120 Q	E	BSW	04505920000	Yes	32.1	61.1	80.0	11.0 (8.0)	(7.5 - 9.0)	3415	18	648
	70	LT265/70 R 18	124/121 Q	E	BSW	04505880000	Yes	32.6	60.4	80.0	10.7 (8.0)	(7.0 - 9.0)	3525	18	637
	70	LT275/70 R 18	125/122 Q	E	SRL	04505890000	Yes	33.2	63.5	80.0	11.0 (8.0)	(7.0 - 8.5)	3640	18	627
	70	LT275/70 R 18	125/122 Q	E	BSW	04505900000	Yes	33.2	63.5	80.0	11.0 (8.0)	(7.0 - 8.5)	3640	18	627
	70	LT295/70 R 18	129/126 Q	E	BSW	04505910000	Yes	34.3	69.7	80.0	11.8 (8.5)	(7.5 - 10.0)	4080	18	606
20	12.50	33 X 12.50 R 20 LT	114 Q	E	BSW	04506050000	Yes	33.0	71.5	65.0	12.5 (10.0)	(8.5 - 11.0)	2601	21	630
	12.50	35 X 12.50 R 20 LT	121 Q	E	SRL	04506060000	Yes	35.0	76.2	65.0	12.5 (10.0)	(8.5 - 11.0)	3195	21	594
	12.50	35 X 12.50 R 20 LT	121 Q	E	BSW	04506070000	Yes	35.0	76.2	65.0	12.5 (10.0)	(8.5 - 11.0)	3195	21	594
	13.50	37 X 13.50 R 20 LT	127 Q	E	SRL	04506080000	Yes	37.0	85.0	65.0	13.6 (11.0)	(8.5 - 11.0)	3860	21	561
	13.50	37 X 13.50 R 20 LT	127 Q	E	BSW	04506090000	Yes	37.0	85.0	65.0	13.6 (11.0)	(8.5 - 11.0)	3860	21	561
	55	LT295/55 R 20	123/120 Q	E	BSW	04506010000	Yes	32.8	68.7	80.0	12.2 (9.5)	(8.0 - 10.0)	3415	18	634
	55	LT305/55 R 20	121/118 Q	E	SRL	04506030000	Yes	33.2	71.2	65.0	12.4 (9.5)	(8.5 - 11.0)	3195	19	626

BSW = Black Sidewall



GRABBER™ X³ | Product Data

LT/SUV | ALL-SEASON | MUD-TERRAIN

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ND S)	REVS PER MILE
20	55	LT305/55 R 20	121/118 Q	E	BSW	04506040000	Yes	33.2	70.6	65.0	12.4 (9.5)	(8.5 - 11.0)	3195	19	626
	65	LT275/65 R 20	126/123 Q	E	BSW	04505980000	Yes	34.1	66.7	80.0	11.0 (8.0)	(7.5 - 9.5)	3750	18	610
	65	LT295/65 R 20	129/126 Q	E	SRL	04505990000	Yes	35.1	69.5	80.0	11.8 (8.5)	(8.0 - 10.0)	4080	18	592
	65	LT295/65 R 20	129/126 Q	E	BSW	04506000000	Yes	35.1	69.2	80.0	11.8 (8.5)	(8.0 - 10.0)	4080	18	592
22	13.50	37 X 13.50 R 22 LT	123 Q	E	SRL	04509840000	Yes	37.0	88.1	65.0	13.6 (11.0)	(8.5 - 12.0)	3415	21	561

BSW = Black Sidewall

GENERAL TIRE  TM

DELIVERS



DELIVERS

for finding alternate routes.

Our **winter** products are developed for superior traction on wet, snow and ice covered roads.



AltiMAX™ Arctic¹²



Grabber™ Arctic



Grabber™ Arctic LT





PASSENGER & CROSSOVER | WINTER | TOURING

ALTIMAX™ ARCTIC¹²

Rim Diameter



14" - 19"

Aspect Ratio



45 - 70

Tread Pattern




Directional

TREADWEAR	TRACTION	TEMPERATURE	SPEED
--	--	--	T

Benefits

- Excellent grip in low temperatures
- Reliable braking on wet, snow or ice-covered roads
- Superb steering response and dry handling
- Long-lasting treadwear



3-Peak Mountain Snowflake

Meets the severe snow service requirements of the U.S. Tire Manufacturers Association (USTMA) and the Tire and Rubber Association of Canada (TRAC).



Pinned for Winter Studs

Stud length for metric sizes: 11mm (TSMI #12). Stud size listed on the tire's sidewall.

Sample Vehicle Fitments Include:

- Audi
- BMW
- Chevrolet
- Ford
- GM
- Honda
- Hyundai
- Kia
- Nissan
- Toyota



CUSTOMER SATISFACTION TRIAL

Or the first 2/32^{nds} of tread. See warranty manual for complete details.

ALTIMAX™ ARCTIC¹² | Product Data

PASSENGER & CROSSOVER | WINTER | TOURING

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ^{nds})	REVS PER MILE
14	65	175/65 R 14	86 T	XL	BSW	15502980000	No	23.0	16.4	51.0	7.0 (5.0)	(5.0 - 6.0)	1168	12	905
	65	185/65 R 14	90 T	XL	BSW	15502920000	No	23.5	16.4	51.0	7.4 (5.5)	(5.0 - 6.5)	1323	12	885
	70	175/70 R 14	88 T	XL	BSW	15503160000	No	23.6	16.6	51.0	7.0 (5.0)	(4.5 - 6.0)	1235	12	879
	70	185/70 R 14	92 T	XL	BSW	15503040000	No	24.2	19.2	51.0	7.4 (5.5)	(4.5 - 6.0)	1389	12	859
15	60	185/60 R 15	88 T	XL	BSW	15502930000	No	23.7	18.0	51.0	7.4 (5.5)	(5.0 - 6.5)	1235	12	875
	60	195/60 R 15	92 T	XL	BSW	15502780000	No	24.2	20.1	51.0	7.9 (6.0)	(5.5 - 7.0)	1389	12	858
	65	175/65 R 15	88 T	XL	BSW	15503110000	No	24.0	17.5	51.0	7.0 (5.0)	(5.0 - 6.0)	1235	12	867
	65	185/65 R 15	92 T	XL	BSW	15502800000	No	24.5	18.4	51.0	7.4 (5.5)	(5.0 - 6.5)	1389	12	849
	65	195/65 R 15	95 T	XL	BSW	15502760000	No	25.0	20.2	51.0	7.9 (6.0)	(5.5 - 7.0)	1521	12	832
	65	205/65 R 15	99 T	XL	BSW	15502880000	No	25.5	21.9	51.0	8.2 (6.0)	(5.5 - 7.5)	1709	12	815
	70	205/70 R 15	100 T	XL	BSW	15503030000	Yes	26.3	24.4	51.0	8.2 (6.0)	(5.0 - 7.0)	1764	12	790
	70	215/70 R 15	103 T	XL	BSW	15502960000	No	26.9	26.4	51.0	8.7 (6.5)	(5.5 - 7.0)	1929	12	774
16	55	205/55 R 16	94 T	XL	BSW	15502500000	No	24.9	21.7	51.0	8.4 (6.5)	(5.5 - 7.5)	1477	12	835
	55	215/55 R 16	97 T	XL	BSW	15502900000	No	25.3	23.3	51.0	8.9 (7.0)	(6.0 - 7.5)	1609	12	821
	55	225/55 R 16	99 T	XL	BSW	15503150000	No	25.7	24.9	51.0	9.2 (7.0)	(6.0 - 8.0)	1709	12	807
	60	205/60 R 16	96 T	XL	BSW	15502790000	No	25.7	23.3	51.0	8.2 (6.0)	(5.5 - 7.5)	1565	12	809
	60	215/60 R 16	99 T	XL	BSW	15502510000	No	26.2	23.7	51.0	8.7 (6.5)	(6.0 - 7.5)	1709	12	794
	60	225/60 R 16	102 T	XL	BSW	15502840000	No	26.6	26.6	51.0	9.0 (6.5)	(6.0 - 8.0)	1874	12	780
	60	235/60 R 16	104 T	XL	BSW	15503130000	Yes	27.1	30.6	51.0	9.4 (7.0)	(6.5 - 8.5)	1984	12	766
	65	205/65 R 16	99 T	XL	BSW	15502970000	No	26.5	22.8	51.0	8.2 (6.0)	(5.5 - 7.5)	1709	12	784
	65	215/65 R 16	102 T	XL	BSW	15502850000	Yes	27.0	26.4	51.0	8.7 (6.5)	(6.0 - 7.5)	1874	12	769
	65	225/65 R 16	104 T	XL	BSW	15503020000	No	27.5	29.2	51.0	9.0 (6.5)	(6.0 - 8.0)	1984	12	755
	70	215/70 R 16	104 T	XL	BSW	15502810000	Yes	27.9	29.3	51.0	8.7 (6.5)	(5.5 - 7.0)	1984	12	746
70	225/70 R 16	107 T	XL	BSW	15503080000	Yes	28.4	30.0	51.0	9.0 (6.5)	(6.0 - 7.5)	2149	12	731	
17	45	215/45 R 17	91 T	XL	BSW	15502990000	Yes	24.6	21.9	51.0	8.4 (7.0)	(7.0 - 8.0)	1356	12	844
	45	225/45 R 17	94 T	XL	BSW	15502950000	Yes	25.0	23.1	51.0	8.9 (7.5)	(7.0 - 8.5)	1477	12	832
	45	235/45 R 17	97 T	XL	BSW	15503060000	Yes	25.3	25.7	51.0	9.3 (8.0)	(7.5 - 9.0)	1609	12	820
	50	205/50 R 17	93 T	XL	BSW	15502890000	Yes	25.1	22.4	51.0	8.4 (6.5)	(5.5 - 7.5)	1433	12	829
	50	215/50 R 17	95 T	XL	BSW	15503050000	Yes	25.5	24.5	51.0	8.9 (7.0)	(6.0 - 7.5)	1521	12	816
	50	225/50 R 17	98 T	XL	BSW	15503100000	Yes	25.9	25.2	51.0	9.2 (7.0)	(6.0 - 8.0)	1653	12	803
	55	215/55 R 17	98 T	XL	BSW	15502830000	No	26.3	23.7	51.0	8.9 (7.0)	(6.0 - 7.5)	1653	12	790
	55	225/55 R 17	101 T	XL	BSW	15502910000	No	26.7	26.0	51.0	9.2 (7.0)	(6.0 - 8.0)	1819	12	777
	55	235/55 R 17	103 T	XL	BSW	15502940000	No	27.2	30.4	51.0	9.6 (7.5)	(6.5 - 8.5)	1929	12	764
	60	215/60 R 17	100 T	XL	BSW	15503000000	Yes	27.2	25.6	51.0	8.7 (6.5)	(6.0 - 7.5)	1764	12	765
	60	225/60 R 17	103 T	XL	BSW	15502820000	Yes	27.6	28.3	51.0	9.0 (6.5)	(6.0 - 8.0)	1929	12	752
	60	235/60 R 17	106 T	XL	BSW	15503140000	Yes	28.1	31.8	51.0	9.4 (7.0)	(6.5 - 8.5)	2094	12	739
	65	215/65 R 17	103 T	XL	BSW	15503090000	Yes	28.0	26.4	51.0	8.7 (6.5)	(6.0 - 7.5)	1929	12	742
	65	225/65 R 17	106 T	XL	BSW	15502770000	Yes	28.5	30.4	51.0	9.0 (6.5)	(6.0 - 8.0)	2094	12	729
	65	235/65 R 17	108 T	XL	BSW	15503010000	Yes	29.0	32.4	51.0	9.4 (7.0)	(6.5 - 8.5)	2205	12	716
18	45	225/45 R 18	95 T	XL	BSW	15503170000	Yes	26.0	24.9	51.0	8.9 (7.5)	(7.0 - 8.5)	1521	12	800

BSW = Black Sidewall



ALTIMAX™ ARCTIC¹² | Product Data

PASSENGER & CROSSOVER | WINTER | TOURING

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ND S)	REVS PER MILE
18	45	235/45 R 18	98 T	XL	BSW	15503220000	Yes	26.3	25.6	51.0	9.3 (8.0)	(7.5 - 9.0)	1653	12	789
	50	225/50 R 18	99 T	XL	BSW	15503210000	Yes	26.9	26.4	51.0	9.2 (7.0)	(6.0 - 8.0)	1709	12	773
	55	225/55 R 18	102 T	XL	BSW	15503190000	Yes	27.7	27.6	51.0	9.2 (7.0)	(6.0 - 8.0)	1874	12	749
	55	235/55 R 18	104 T	XL	BSW	15503120000	Yes	28.2	28.7	51.0	9.6 (7.5)	(6.5 - 8.5)	1984	12	737
	60	225/60 R 18	104 T	XL	BSW	15503180000	Yes	28.6	29.7	51.0	9.0 (6.5)	(6.0 - 8.0)	1984	12	726
	60	235/60 R 18	107 T	XL	BSW	15503070000	Yes	29.1	32.1	51.0	9.4 (7.0)	(6.5 - 8.5)	2149	12	714
19	55	225/55 R 19	103 T	XL	BSW	15503200000	Yes	28.7	28.8	51.0	9.2 (7.0)	(6.0 - 8.0)	1929	12	723

BSW = Black Sidewall

GENERAL TIRE  TM

DELIVERS



LT/SUV | WINTER | TOURING

GRABBER™ ARCTIC



TREADWEAR	TRACTION	TEMPERATURE	SPEED
--	--	--	T

Benefits

- Excellent grip in low temperatures
- Reliable braking on wet, snow or ice-covered roads
- Superb steering response and dry handling
- Robust durability
- Long-lasting treadwear



**DURAGEN
EG
TECHNOLOGY**

- Enhances strength and durability
- Delivers cut-and-chip resistance
- Extends tread life



3-Peak Mountain Snowflake
Meets the severe snow service requirements of the U.S. Tire Manufacturers Association (USTMA) and the Tire and Rubber Association of Canada (TRAC).



Pinned for Winter Studs
Stud length for metric sizes: 11mm (TSMI #12). Stud size listed on the tire's sidewall.

Sample Vehicle Fitments Include:

- Chevrolet
- Ford
- Nissan
- Ram
- Toyota



CUSTOMER SATISFACTION TRIAL

Or the first 2/32^{nds} of tread. See warranty manual for complete details.

GRABBER™ ARCTIC | Product Data

LT/SUV | WINTER | TOURING

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ^{nds})	REVS PER MILE
16	70	235/70 R 16	109 T	XL	BSW	15503280000	Yes	29.0	33.0	51.0	9.4 (7.0)	(6.0 - 8.0)	2271	12	718
	70	265/70 R 16	116 T	XL	BSW	15503340000	Yes	30.6	39.3	51.0	10.7 (8.0)	(7.0 - 9.0)	2756	12	679
	75	245/75 R 16	115 T	XL	BSW	15503330000	Yes	30.5	35.1	51.0	9.8 (7.0)	(6.5 - 8.0)	2679	12	682
17	65	245/65 R 17	111 T	XL	BSW	15503260000	Yes	29.5	34.7	51.0	9.8 (7.0)	(7.0 - 8.5)	2403	12	703
	65	265/65 R 17	116 T	XL	BSW	15503370000	Yes	30.6	36.6	51.0	10.7 (8.0)	(7.5 - 9.5)	2756	12	680
	70	245/70 R 17	114 T	XL	BSW	15503290000	Yes	30.5	34.8	51.0	9.8 (7.0)	(6.5 - 8.0)	2601	12	681
	70	265/70 R 17	116 T	XL	BSW	15502540000	Yes	31.6	39.2	51.0	10.7 (8.0)	(7.0 - 9.0)	2756	12	657
18	55	255/55 R 18	109 T	XL	BSW	15502560000	Yes	29.0	33.8	51.0	10.4 (8.0)	(7.0 - 9.0)	2271	12	715
	60	245/60 R 18	109 T	XL	BSW	15503310000	Yes	29.6	34.5	51.0	9.8 (7.0)	(7.0 - 8.5)	2271	12	702
	60	265/60 R 18	114 T	XL	BSW	15503350000	Yes	30.5	38.1	51.0	10.7 (8.0)	(7.5 - 9.5)	2601	12	681
	65	255/65 R 18	115 T	XL	BSW	15503380000	Yes	31.1	36.9	51.0	10.2 (7.5)	(7.0 - 9.0)	2679	12	669
	65	265/65 R 18	116 T	XL	BSW	15503360000	Yes	31.6	40.5	51.0	10.7 (8.0)	(7.5 - 9.5)	2756	12	658
	65	275/65 R 18	116 T	XL	BSW	15503300000	Yes	32.1	40.7	51.0	11.0 (8.0)	(7.5 - 9.5)	2756	12	648
20	55	275/55 R 20	117 T	XL	BSW	15503270000	Yes	31.9	39.9	51.0	11.2 (8.5)	(7.5 - 9.5)	2833	12	651
	60	275/60 R 20	116 T	XL	BSW	15503320000	Yes	33.0	41.5	51.0	11.0 (8.0)	(7.5 - 9.5)	2756	12	630

BSW = Black Sidewall





LT/SUV | WINTER | ALL-TERRAIN

GRABBER™ ARCTIC LT

Rim Diameter



16" - 20"

Aspect Ratio



65 - 75

Tread Pattern



Symmetric

TREADWEAR	TRACTION	TEMPERATURE	SPEED
--	--	--	R

Benefits

- Symmetric tread pattern allows for the tire to be rotated, promoting long, even tread life
- Excellent grip in low temperatures
- Reliable braking on wet, snow or ice-covered roads
- Robust durability
- Superb steering response and dry handling
- Long-lasting treadwear



CUSTOMER SATISFACTION TRIAL

Or the first 2/32^{nds} of tread. See warranty manual for complete details.



DURAGEN
EG
TECHNOLOGY

- Enhances strength and durability
- Delivers cut-and-chip resistance
- Extends tread life



3-Peak Mountain Snowflake
Meets the severe snow service requirements of the U.S. Tire Manufacturers Association (USTMA) and the Tire and Rubber Association of Canada (TRAC).



Pinned for Winter Studs
Stud length for metric sizes:
12mm (TSMI #13)

Sample Vehicle Fitments Include:

- Chevrolet: Silverado, Tahoe, Express Vans & Suburban
- Ford: F-Series Pickup Trucks, Econoline Vans, Excursion & Expedition
- GMC: Sierra, Savanna & Yukon
- Ram: Pickup Trucks & Vans

GRABBER™ ARCTIC LT | Product Data

LT/SUV | WINTER | ALL-TERRAIN

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ^{nds})	REVS PER MILE
16	75	LT225/75 R 16	115/112 R	E	BSW	04504420000	Yes	29.3	41.9	80.0	8.8 (6.0)	(6.0 - 7.0)	2680	16	709
	75	LT245/75 R 16	120/116 R	E	BSW	04504440000	Yes	30.5	46.4	80.0	9.8 (7.0)	(6.5 - 8.0)	3085	16	682
	75	LT265/75 R 16	123/120 R	E	BSW	04504450000	Yes	31.6	51.4	80.0	10.5 (7.5)	(7.0 - 8.0)	3415	16	656
17	70	LT245/70 R 17	119/116 R	E	BSW	04504460000	Yes	30.5	49.2	80.0	9.8 (7.0)	(6.5 - 8.0)	3000	16	681
	70	LT265/70 R 17	121/118 R	E	BSW	04504480000	Yes	31.6	53.4	80.0	10.7 (8.0)	(7.0 - 8.5)	3195	16	657
	75	LT245/75 R 17	121/118 R	E	BSW	04504470000	Yes	31.5	49.4	80.0	9.8 (7.0)	(6.5 - 7.5)	3195	16	660
18	65	LT275/65 R 18	123/120 R	E	BSW	04504500000	Yes	32.1	54.8	80.0	11.0 (8.0)	(7.5 - 9.0)	3415	16	648
	70	LT265/70 R 18	124/121 R	E	BSW	04504490000	Yes	32.6	54.7	80.0	10.7 (8.0)	(7.0 - 9.0)	3525	16	637
	70	LT275/70 R 18	125/122 R	E	BSW	04504510000	Yes	33.2	56.6	80.0	11.0 (8.0)	(7.0 - 8.5)	3640	16	627
20	65	LT275/65 R 20	126/123 R	E	BSW	04504520000	Yes	34.1	59.8	80.0	11.0 (8.0)	(7.5 - 9.5)	3750	16	610

BSW = Black Sidewall





DELIVERS

for getting the job done.

Our fleet-applicable products deliver the level of reliability that **government** and **commercial** vehicles demand.



Grabber™ HD



Grabber™ HD Van



G-MAX™ Justice



G-MAX™ Justice AW





GOVERNMENT/FLEET & LT/SUV | ALL-SEASON | COMMERCIAL

GRABBER™ HD

Rim Diameter



16" - 18"

Aspect Ratio



60 - 85

Tread Pattern



Symmetric

TREADWEAR	TRACTION	TEMPERATURE	SPEED
--	--	--	R & S



DURAGEN
EGG
TECHNOLOGY

- Enhances strength and durability
- Delivers cut-and-chip resistance
- Extends tread life

Sample Vehicle Fitments Include:

- Various Work Trucks & Vans

Benefits

- Additional rubber gauge added to the sidewall to increase robustness against curbs and other sidewall abrasions
- Exceptional traction, on and off the work site
- Dependable stability and handling under loaded conditions
- Robust durability with enhanced sidewall protection
- Up to 25% better treadwear versus the leading competitor*



CUSTOMER SATISFACTION TRIAL

Or the first 2/32^{nds} of tread. See warranty manual for complete details.

*Based on internal treadwear test results compared to the Firestone Transforce HT in the size LT245/70R17 119/116R. On road results may vary.

GRABBER™ HD | Product Data

GOVERNMENT/FLEET & LT/SUV | ALL-SEASON | COMMERCIAL

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ^{nds})	REVS PER MILE
16	75	225/75 R 16 C	121/120 R	E	BSW	04507240000	No	29.3	38.8	90.0	8.8 (6.0)	(6.0 - 7.0)	3195	12	709
	75	LT225/75 R 16	115/112 R	E	BSW	04507160000	Yes	29.3	40.1	80.0	8.8 (6.0)	(6.0 - 7.0)	2680	14	709
	75	LT245/75 R 16	120/116 S	E	BSW	04507180000	Yes	30.5	44.3	80.0	9.8 (7.0)	(6.5 - 8.0)	3085	14	682
	75	LT265/75 R 16	123/120 R	E	BSW	04507190000	Yes	31.6	49.0	80.0	10.5 (7.5)	(7.0 - 8.0)	3415	14	656
	85	LT215/85 R 16	115/112 R	E	BSW	04507140000	Yes	30.4	41.6	80.0	8.5 (6.0)	(5.5 - 7.0)	2680	14	684
	85	LT235/85 R 16	120/116 R	E	BSW	04507170000	Yes	31.7	44.4	80.0	9.3 (6.5)	(6.0 - 7.5)	3085	14	655
17	70	LT245/70 R 17	119/116 R	E	BSW	04507210000	Yes	30.5	44.4	80.0	9.8 (7.0)	(6.5 - 8.0)	3000	14	681
	70	LT265/70 R 17	121/118 R	E	BSW	04507220000	Yes	31.6	50.8	80.0	10.7 (8.0)	(7.0 - 8.5)	3195	14	657
	75	LT245/75 R 17	121/118 S	E	BSW	04507200000	Yes	31.5	46.5	80.0	9.8 (7.0)	(6.5 - 7.5)	3195	14	660
	80	LT235/80 R 17	120/117 R	E	BSW	04509200000	Yes	31.8	46.7	80.0	9.3 (6.5)	(6.0 - 7.5)	3085	14	653
18	65	LT275/65 R 18	123/120 R	E	BSW	04509170000	Yes	32.1	52.1	80.0	11.0 (8.0)	(7.5 - 9.0)	3415	14	648
	70	LT265/70 R 18	124/121 R	E	BSW	04509180000	Yes	32.6	51.0	80.0	10.7 (8.0)	(7.0 - 9.0)	3525	14	637
	70	LT275/70 R 18	125/122 S	E	BSW	04509190000	Yes	33.2	54.3	80.0	11.0 (8.0)	(7.0 - 8.5)	3640	14	627

BSW = Black Sidewall





GOVERNMENT/FLEET & CARGO VAN | ALL-SEASON | COMMERCIAL

GRABBER™ HD VAN

Rim Diameter



15" - 16"

Aspect Ratio



60 - 75

Tread Pattern



Symmetric

TREADWEAR	TRACTION	TEMPERATURE	SPEED
--	--	--	R & T


Benefits

- Balanced performance on wet and dry roads
- Dependable stability and handling under loaded conditions
- Robust durability with enhanced sidewall protection
- Up to 25% better treadwear versus the leading competitors*



DURAGEN
EGG
TECHNOLOGY

- Enhances strength and durability
- Delivers cut-and-chip resistance
- Extends tread life



Sidewall Curb Guard

Additional rubber gauge added to the sidewall to increase robustness against curbs and other sidewall abrasions.

Sample Vehicle Fitments Include:

- Various Work Trucks & Vans



CUSTOMER SATISFACTION TRIAL

Or the first 2/32^{nds} of tread. See warranty manual for complete details.

*Based on internal treadwear test results compared to the Goodyear Wrangler Fortitude HT, Firestone Transforce CV, and the Cooper Discoverer HT3 in the size 235/65R16C 121/119R. On road results may vary.

GRABBER™ HD VAN | Product Data

GOVERNMENT/FLEET & CARGO VAN | ALL-SEASON | COMMERCIAL

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ^{nds})	REVS PER MILE
15	60	185/60 R 15 C	94/92 T	C	BSW	04603440000	No	23.7	21.0	64.0	7.4 (5.5)	(5.5 - 6.0)	1475	14	875
	70	195/70 R 15 C	104/102 R	D	BSW	04603450000	No	25.7	26.0	75.0	7.9 (6.0)	(5.0 - 6.0)	1985	14	807
16	65	235/65 R 16 C	121/119 R	E	BSW	04603460000	No	28.0	37.0	93.0	9.4 (7.0)	(6.5 - 7.5)	3195	14	741
	75	195/75 R 16 C	107/105 R	D	BSW	04603430000	No	27.5	28.8	79.0	7.7 (5.5)	(5.0 - 6.0)	2150	14	755

BSW = Black Sidewall





GOVERNMENT/FLEET | ALL-SEASON | HIGH-SPEED PURSUIT

G-MAX™ JUSTICE

Rim Diameter



16" - 20"

Aspect Ratio



50 - 60

Tread Pattern



Asymmetric

TREADWEAR	TRACTION	TEMPERATURE	SPEED
440	AA	A	V & W

Sample Vehicle Fitments Include:

- Chevrolet Caprice: 235/50ZR18
- Chevrolet Impala: 225/60R16, 235/55ZR17
- Chevrolet Tahoe: 265/60R17, 275/55R20
- Dodge Charger: 245/55R18, 225/60ZR18
- Dodge Durango: 255/60R18
- Ford Crown Victoria: 225/60R16, 235/55ZR17
- Ford Interceptor: 225/60R16, 235/55ZR17, 245/55R18, 255/60R18

Benefits

- Up to 15% longer-lasting treadwear versus the leading all-season pursuit competitor*
- Up to 15% better wet braking performance versus the leading all-season pursuit competitor*

*Based on internal test results compared to the Goodyear Eagle RS-A in the size P235/55R17 98W. On road results may vary.

G-MAX™ JUSTICE | Product Data

GOVERNMENT & FLEET | ALL-SEASON | HIGH-SPEED PURSUIT

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ND PS)	REVS PER MILE
16	60	225/60 R 16	98 V	SL	BSW	15553910000	Yes	26.6	25.4	51.0	9.0 (6.5)	(6.0 - 8.0)	1653	10	780
17	55	235/55 ZR 17	99 W	SL	BSW	15553940000	Yes	27.2	27.5	51.0	9.6 (7.5)	(6.5 - 8.5)	1709	10	764
	60	265/60 R 17	108 V	SL	BSW	15553960000	Yes	29.5	35.5	51.0	10.7 (8.0)	(7.5 - 9.5)	2205	10	704
18	50	235/50 ZR 18	101 W	XL	BSW	15553930000	Yes	27.3	26.2	51.0	9.6 (7.5)	(6.5 - 8.5)	1819	10	762
	55	245/55 R 18	103 V	SL	BSW	15553950000	Yes	28.6	30.7	51.0	10.0 (7.5)	(7.0 - 8.5)	1929	10	726
	60	225/60 ZR 18	100 W	SL	BSW	15553920000	Yes	28.6	29.1	51.0	9.0 (6.5)	(6.0 - 8.0)	1764	10	726
	60	255/60 R 18	112 V	XL	BSW	04505550000	Yes	30.0	33.7	51.0	10.2 (7.5)	(7.0 - 9.0)	2469	10	691
20	55	275/55 R 20	113 V	SL	BSW	15590810000	Yes	31.9	40.9	51.0	11.2 (8.5)	(7.5 - 9.5)	2535	11	651

BSW = Black Sidewall





GOVERNMENT/FLEET | ALL-WEATHER | HIGH-SPEED PURSUIT

G-MAX™ JUSTICE AW

Rim Diameter



17" - 20"

Aspect Ratio




50 - 60

Tread Pattern



Symmetric

TREADWEAR	TRACTION	TEMPERATURE	SPEED
540	A	A	V



3-Peak Mountain Snowflake
Meets the severe snow service requirements of the U.S. Tire Manufacturers Association (USTMA) and the Tire and Rubber Association of Canada (TRAC).

Sample Vehicle Fitments Include:

- Chevrolet Caprice: 235/50R18
- Chevrolet Impala: 235/55R17
- Chevrolet Tahoe: 265/60R17, 275/55R20
- Dodge Charger: 225/60R18, 245/55R18
- Dodge Durango: 255/60R18
- Ford Crown Victoria; 235/55R17
- Ford Interceptor: 235/55R17, 245/55R18, 255/60R18

Benefits

- Up to 15% longer-lasting treadwear versus the leading all-weather pursuit competitor*
- Up to 18% better wet braking performance versus the leading all-weather pursuit competitor*
- Better winter performance versus the leading all-weather pursuit competitor**

*Based on internal test results compared to the Goodyear Eagle Enforcer All Weather in the size 245/55R18 103V. On road results may vary.

**Based on internal tire test results of the following key performance categories: snow handling, snow traction, ice acceleration and ice braking compared to the Goodyear Eagle Enforcer All Weather in the size 245/55R18 103V. On road results may vary.

G-MAX™ JUSTICE AW | Product Data

GOVERNMENT & FLEET | ALL-WEATHER | HIGH-SPEED PURSUIT

RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM) (IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ^{nds})	REVS PER MILE
17	55	235/55 R 17	99 V	SL	BSW	15578210000	Yes	27.2	27.4	51.0	9.6 (7.5)	(6.5 - 8.5)	1709	10	764
	60	265/60 R 17	108 V	SL	BSW	15578230000	Yes	29.5	36.5	51.0	10.7 (8.0)	(7.5 - 9.5)	2205	11	704
18	50	235/50 R 18	101 V	XL	BSW	15578200000	Yes	27.3	27.2	51.0	9.6 (7.5)	(6.5 - 8.5)	1819	11	762
	55	245/55 R 18	103 V	SL	BSW	15578220000	Yes	28.6	30.8	51.0	10.0 (7.5)	(7.0 - 8.5)	1929	11	726
	60	225/60 R 18	100 V	SL	BSW	15578190000	Yes	28.6	29.1	51.0	9.0 (6.5)	(6.0 - 8.0)	1764	10	726
	60	255/60 R 18	112 V	XL	BSW	15578240000	Yes	30.0	32.9	51.0	10.2 (7.5)	(7.0 - 9.0)	2469	11	691
20	55	275/55 R 20	113 V	SL	BSW	15578250000	Yes	31.9	40.9	51.0	11.2 (8.5)	(7.5 - 9.5)	2535	11	651

BSW = Black Sidewall



ORIGINAL EQUIPMENT



Ameritrac™
LT/SUV | All-Season | Touring



Ameritrac™ TR
LT/SUV | All-Season | All-Terrain



Grabber™ APT
LT/SUV | All-Season | All-Terrain



Grabber™ A/T^x
LT/SUV | All-Season | All-Terrain



Grabber™ HTS
Crossover & LT/SUV | All-Season | Touring



Grabber™ HTS⁶⁰
Crossover & LT/SUV | All-Season | Touring

OE PRODUCT LINE	RIM DIA (IN)	ASPECT RATIO (SERIES)	TIRE SIZE	LOAD/SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	RIM PROTECTION	TIRE DIA (IN)	TIRE WT (LBS)	MAX PSI	OVERALL SECTION WIDTH (MEASURING RIM)-(IN)	APPROVED RIM WIDTHS (IN)	MAX LOAD (LBS)	TREAD DEPTH (32 ND S)	REVS PER MILE	UTQG
Ameritrac™																	
DODGE	17	80	LT235/80 R 17	120/117 R	E	BSW	04501890000	No	31.8	47.6	80.0	9.3 (6.5)	(6.0 - 7.5)	3086	14	653	None
Ameritrac™ TR																	
DODGE	17	80	LT235/80 R 17	120/117 R	E	OWL	04501870000	No	31.8	50.4	80.0	9.3 (6.5)	(6.0 - 7.5)	3086	16	653	None
		80	LT235/80 R 17	120/117 R	E	BSW	04501880000	No	31.8	49.9	80.0	9.3 (6.5)	(6.0 - 7.5)	3086	16	653	None
Grabber™ A/T^X																	
FORD	17	70	LT 265/70 R 17	112/109 T	C	BSW	04509790000	No	31.6	44.9	50.0	10.7 (8.0)	(7.0 - 8.5)	2470	16	657	None
		70	275/70 R 18	116 S	SL	BSW	04492430000	No	33.2	45.5	44.0	11.0 (8.0)	(7.0 - 9.0)	2756	14	627	640 A B
	18	70	275/70 R 18	116 S	SL	BSW	04509780000	No	33.2	44.3	44.0	11.0 (8.0)	(7.0 - 9.0)	2756	14	627	640 A B
Grabber™ APT																	
FORD	17	70	LT 265/70 R 17	112/109 S	C	BSW	15570730000	No	31.6	40.4	50.0	10.7 (8.0)	(7.0 - 8.5)	2470	12	657	None
		70	LT 265/70 R 18	113/110 S	C	OWL	04509860000	No	32.6	43.1	50.0	10.7 (8.0)	(7.0 - 9.0)	2535	12	637	None
	70	LT 265/70 R 18	113/110 S	C	BSW	04492580000	No	32.6	43.9	50.0	10.7 (8.0)	(7.0 - 9.0)	2535	13	637	None	
NISSAN	18	65	LT 275/65 R 18	123/120 R	E	BSW	04507640000	No	32.1	53.4	80.0	11.0 (8.0)	(7.5 - 9.0)	3415	15	647	None
		70	P 275/70 R 18	116 S	SL	OWL	04503130000	No	33.2	41.9	44.0	11.0 (8.0)	(7.0 - 9.0)	2756	12	626	520 A B
	70	P 275/70 R 18	116 S	SL	BSW	04492870000	No	33.2	40.3	44.0	11.0 (8.0)	(7.0 - 9.0)	2756	13	627	520 A B	
Grabber™ HTS																	
CHEVROLET	16	75	LT225/75 R 16	115/112 S	E	BSW	04501200000	No	29.3	38.7	80.0	8.8 (6.0)	(6.0 - 7.0)	2680	13	709	None
	17	70	255/70 R 17	112 S	SL	BSW	04509000000	No	31.1	33.1	44.0	10.2 (7.5)	(6.5 - 8.5)	2469	11	669	640 A B
GMC	17	70	P245/70 R 17	108 S	SL	BSW	15448420000	No	30.5	31.6	44.0	9.8 (7.0)	(6.5 - 8.0)	2204	11	681	640 A B
NISSAN	18	70	265/70 R 18	116 S	SL	OWL	04503190000	No	32.6	39.3	44.0	10.7 (8.0)	(7.0 - 9.0)	2755	11	637	640 A B
		70	265/70 R 18	116 S	SL	BSW	04492880000	No	32.6	37.8	44.0	10.7 (8.0)	(7.0 - 9.0)	2756	11	637	640 A B
	20	60	LT 265/60 R 20	121/118 R	E	BSW	04503240000	No	32.5	53.4	80.0	10.7 (8.0)	(7.5 - 9.5)	3195	12	639	None
Grabber™ HTS⁶⁰																	
CHEVROLET	20	60	275/60 R 20	115 S	SL	BSW	04505640000	No	33.0	40.7	44.0	11.0 (8.0)	(7.5 - 9.5)	2679	11	630	680 A B
FORD		60	275/60 R 20	116 T	XL	BSW	04509800000	No	33.0	34.3	51.0	11.0 (8.0)	(7.5 - 9.5)	2756	10	630	620 A B
GMC		60	275/60 R 20	115 S	SL	BSW	04505270000	No	33.0	36.4	44.0	11.0 (8.0)	(7.5 - 9.5)	2679	11	630	620 A B
FORD	22	45	285/45 R 22	114 H	XL	BSW	04491490000	No	32.1	38.0	51.0	11.2 (9.5)	(9.0 - 10.5)	2601	10	647	660 A A
		50	275/50 R 22	115 T	XL	BSW	04490900000	No	32.8	39.1	51.0	11.2 (8.5)	(7.5 - 9.5)	2679	10	633	680 A B

BSW = Black Sidewall | OWL = Outlined White Letter

VEHICLE FITMENT	ARTICLE NUMBER	MARKET LINE	TIRE SIZE	YEARS SELECTED AS ORIGINAL EQUIPMENT					
CHEVROLET									
EXPRESS PASSENGER	04501200000	Grabber™ HTS	LT225/75 R 16	2019	2020	2021	2022	2023	
SILVERADO	04505640000	Grabber™ HTS ⁶⁰	275/60 R 20	2019	2020	2021	2022	--	
SILVERADO	04509000000	Grabber™ HTS	255/70 R 17	2019	2020	2021	2022	2023	
DODGE									
RAM	04501870000	Ameritrac™ TR	LT235/80 R 17	2019	--	--	--	--	
RAM	04501880000	Ameritrac™ TR	LT235/80 R 17	2019	--	--	--	--	
RAM	04501890000	Ameritrac™	LT235/80 R 17	2019	--	--	--	--	
FORD									
BRONCO	04509790000	Grabber™ A/TX	LT 265/70 R 17	--	--	2021	2022	2023	
EXPEDITION	04491490000	Grabber™ HTS ⁶⁰	285/45 R 22	--	--	--	2022	2023	
F-150	04490900000	Grabber™ HTS ⁶⁰	275/50 R 22	--	--	2021	2022	2023	
F-150	04492430000	Grabber™ A/TX	275/70 R 18	--	--	--	2022	2023	
F-150	04492580000	Grabber™ APT	LT 265/70 R 18	--	--	--	2022	2023	
F-150	04509780000	Grabber™ A/TX	275/70 R 18	--	--	2021	2022	--	
F-150	04509800000	Grabber™ HTS ⁶⁰	275/60 R 20	--	--	--	2022	2023	
F-150	04509860000	Grabber™ APT	LT 265/70 R 18	--	2020	2021	2022	--	
F-150	15570730000	Grabber™ APT	LT 265/70 R 17	--	--	2021	2022	2023	
GMC									
SILVERADO	04505270000	Grabber™ HTS ⁶⁰	275/60 R 20	--	--	--	2022	2023	
TRAVERSE	15448420000	Grabber™ HTS	P245/70 R 17	2019	--	--	--	--	
NISSAN									
TITAN	04492870000	Grabber™ APT	P 275/70 R 18	--	--	--	2022	2023	
TITAN	04492880000	Grabber™ HTS	265/70 R 18	--	--	2021	2022	2023	
TITAN	04503130000	Grabber™ APT	P 275/70 R 18	2019	2020	2021	2022	--	
TITAN	04503190000	Grabber™ HTS	265/70 R 18	2019	2020	2021	2022	--	
TITAN	04503240000	Grabber™ HTS	LT 265/60 R 20	2019	2020	2021	2022	2023	
TITAN	04507640000	Grabber™ APT	LT 275/65 R 18	2019	2020	2021	2022	2023	

GENERAL TIRE  TM

DELIVERS

**LIMITED WARRANTY &
ADJUSTMENT POLICY**

LIMITED WARRANTY & ADJUSTMENT POLICY*

Eligibility

- Purchased as replacement tires only.
- Tires used on vehicle originally installed.
- Owner of General Tire brand passenger, LT or special temporary spare tires.

Not Covered

- Road Hazards or repairs.
- Commercial applications.
- Damage resulting from improper maintenance or operation.
- Damage resulting from vehicle mechanical problems.
- Any ride/vibration condition after the first 2/32nds (1.6mm) of an inch of treadwear or 12 months of service, whichever comes first.
- Wear due to improper vehicle alignment.

Coverage

All Passenger General Tires

- Free replacement during 12 months from date of purchase OR first 2/32 treadwear (whichever comes first – mounting and balancing included).
- Pro-rated after free replacement period up to 72 months from date of purchase or wear-out (whichever comes first – mounting and balancing NOT included).

Customer Responsibility

- Responsible for all applicable taxes and local tire disposal fees.
- Must have invoice with date of purchase (DOT tire identification number and/or date of manufacture will be used if invoice not available).

LIMITED TREAD WEAR-OUT COVERAGE*

Eligibility

- Purchased as replacement tires only.
- Tires used on vehicle originally installed.

Products

G-MAX™ AS⁰⁵

- 50,000 miles

AltiMAX™ RT⁴⁵

- 75,000 miles (T & H)
- 65,000 miles (V)

AltiMAX^{365AW}

- 60,000 Miles (H & V)

Grabber™ HTS⁶⁰

- 65,000 miles (S & T)
- 50,000 miles (Includes all Metric sizes with a speed rating of H and above and all LT Metric sizes)

Grabber™ APT

- 60,000 miles (excludes LT Metric and flotation sizes)

Grabber™ A/T^X

- 60,000 miles (excludes LT Metric and flotation sizes)
- 50,000 miles (includes all LT Metric and flotation sizes)

Not Covered

- Road Hazards or repairs.
- Commercial applications.
- Damage resulting from improper maintenance or operation.
- Damage resulting from vehicle mechanical problems.
- Tires not rotated every 6,000 - 8,000 miles.
- Tires in service more than 72 months.

Coverage

- Pro-rated replacement for wearout during mileage coverage OR 72 months of service (whichever comes first).
- Mounting and balancing NOT included.
- Pro-rated price = (mileage received/mileage covered) x dealer selling price = customer price.
- Mileage Warranty for the rear axle of split fitments will be 50% of the standard tread wearout coverage.

Customer Responsibility

- Must have original, up-to-date copy of the Tread Wearout Coverage Rotation Schedule (printed in Limited Warranty Brochure) showing rotation intervals and odometer reading at installation and wear-out.
- Must have original sales invoice with date of purchase.
- Pays for mounting, balancing, and all applicable taxes and local tire disposal fees.

45-DAY CUSTOMER SATISFACTION TRIAL*

Eligibility

- Purchased as replacement tires only.
- Tires used on vehicle originally installed.
- Original Purchaser of a set of four (4) General Tire brand products.

Not Covered

- Road Hazards or repairs.
- Commercial applications.
- Damage resulting from improper maintenance or operation.
- Damage resulting from vehicle mechanical problems.
- Improper mounting or demounting.
- Alterations.

Coverage

- Within 45 days from date of purchase return and exchange all or any one for any reason except for service related conditions.
- Tires must be replaced with Continental or General Tire products.
- If exchanged for higher priced tire, customer pays the difference.
- If exchanged for lower priced tire, customer receives refund.

Customer Responsibility

- Pays for valve stems if required.
- Responsible for all applicable taxes for higher cost tire.
- Must have completed brochure information section.

FOR MORE INFORMATION

For more limited warranty and adjustment policy and safety and maintenance information we encourage you to visit our website at www.GeneralTire.com (customer care link).

For additional safety and maintenance information, please also visit the U.S. Tire Manufacturers Association (USTMA) website at www.ustires.org.

To order physical copies of our warranty brochures please login to the ContiLink (www.ContiLink.com) or ContiCarLink (www.ContiCarLink.com) to access the Dealer Marketing Suite.

Inside Sales: 1-800-321-7575

Consumer Relations: 1-800-847-3349

*Restrictions and limitations apply. See Warranty Brochure for complete details.

PASSENGER TIRE AND LIGHT TRUCK

DEPTH CONVERSION TABLE TO PERCENTAGE OF WEAR

All numbers to the right designate the percentage of usable tread remaining, used to determine credit due to customer toward the purchase of a replacement tire. The numbers to the left designate the percentage of usable tread worn, to determine customer's charge for a replacement tire.

To obtain the remaining tread depth, take three (3) measurements on the tire, one on the inner groove, one on the center and one in the outer groove and then average the three (3) measurements. Locate (below) the tire's original tread depth. Read down and across matching the tire's measured remaining tread depth. Use the percentages shown as a charge and/or credit towards the purchase of a replacement tire.

TREADWEAR CONVERSION TABLE

TREAD DEPTHS IN 32NDS	ORIGINAL TIRE TREAD																			
	9/32	10/32	11/32	12/32	13/32	14/32	15/32	16/32	17/32	18/32	19/32	20/32	21/32	22/32	23/32	24/32	25/32	26/32	27/32	28/32
2/32	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0
3/32	86%/14	88%/12	89%/11	90%/10	91%/9	92%/8	92%/8	93%/7	93%/7	94%/6	94%/6	94%/6	95%/5	95%/5	95%/5	95%/5	96%/4	96%/4	96%/4	96%/4
4/32	71%/29	75%/25	78%/22	80%/20	82%/18	83%/17	85%/15	86%/14	87%/13	88%/12	88%/12	89%/11	89%/11	90%/10	90%/10	91%/9	91%/9	92%/8	92%/8	92%/8
5/32	57%/43	63%/37	67%/33	70%/30	73%/27	75%/25	77%/23	79%/21	80%/20	81%/19	82%/18	83%/17	84%/16	85%/15	86%/14	86%/14	87%/13	88%/12	88%/12	88%/12
6/32	43%/57	50%/50	56%/44	60%/40	64%/36	67%/33	69%/31	71%/29	73%/27	75%/25	76%/24	78%/22	79%/21	80%/20	81%/19	82%/18	83%/17	83%/17	84%/16	85%/15
7/32	29%/71	38%/62	44%/56	50%/50	55%/45	58%/42	62%/38	64%/36	67%/33	69%/31	71%/29	72%/28	74%/26	75%/25	76%/24	77%/23	78%/22	79%/21	80%/20	81%/19
8/32	14%/86	25%/75	33%/67	40%/60	45%/55	50%/50	54%/46	57%/43	60%/40	63%/37	65%/35	67%/33	68%/32	70%/30	71%/29	73%/27	74%/26	75%/25	76%/24	77%/23
9/32	0%/100	13%/87	22%/78	30%/70	36%/64	42%/58	46%/54	50%/50	53%/47	56%/44	59%/41	61%/39	63%/37	65%/35	67%/33	68%/32	70%/30	71%/29	72%/28	73%/27
10/32		0%/100	11%/89	20%/80	27%/73	33%/67	38%/62	43%/57	47%/53	50%/50	53%/47	56%/44	58%/42	60%/40	62%/38	64%/36	65%/35	67%/33	68%/32	69%/31
11/32			0%/100	10%/90	18%/82	25%/75	31%/69	36%/64	40%/60	44%/56	47%/53	50%/50	53%/47	55%/45	57%/43	59%/41	61%/39	62%/38	64%/36	65%/35
12/32				0%/100	9%/91	17%/83	23%/77	29%/71	33%/67	37%/63	41%/59	44%/56	47%/53	50%/50	52%/48	55%/45	57%/43	58%/42	60%/40	62%/38
13/32					0%/100	8%/92	15%/85	21%/79	27%/73	31%/69	35%/65	39%/61	42%/58	45%/55	48%/52	50%/50	52%/48	54%/46	56%/44	58%/42
14/32						0%/100	8%/92	14%/86	20%/80	25%/75	29%/71	33%/67	37%/63	40%/60	43%/57	45%/55	48%/52	50%/50	52%/48	54%/46
15/32							0%/100	7%/93	13%/87	19%/81	24%/76	28%/72	32%/68	35%/65	38%/63	41%/59	43%/57	46%/54	48%/52	50%/50
16/32								0%/100	7%/93	12%/88	18%/82	22%/78	26%/74	30%/70	33%/67	36%/64	39%/61	42%/58	44%/52	46%/54
17/32									0%/100	6%/94	12%/88	17%/83	21%/79	25%/75	29%/71	32%/68	35%/65	38%/62	40%/60	42%/58
18/32										0%/100	6%/94	11%/89	16%/84	20%/80	24%/76	27%/73	30%/70	33%/67	36%/64	38%/62
19/32											0%/100	6%/94	11%/89	15%/85	19%/81	23%/77	26%/74	29%/71	32%/68	35%/65
20/32												0%/100	5%/95	10%/90	14%/86	18%/82	22%/78	25%/75	28%/72	31%/69
21/32													0%/100	5%/95	10%/90	14%/86	17%/83	21%/79	24%/76	27%/73
22/32														0%/100	5%/95	9%/91	13%/87	17%/83	20%/80	23%/77
23/32															0%/100	5%/95	9%/91	12%/88	16%/84	19%/81
24/32																0%/100	4%/96	8%/92	12%/88	15%/85
25/32																	0%/100	4%/96	8%/92	12%/88
26/32																		0%/100	4%/96	8%/92
27/32																			0%/100	4%/96
28/32																				0%/100

REMAINING TIRE TREAD



Dot shows an example of where to take measurements. It is NOT recommended to measure straight across in one location.

AFTER THE SALE, DID YOU COMPLETE YOUR OBLIGATION UNDER THE LAW?

The National Highway Traffic Safety Administration (NHTSA) regulates the use of tire registration forms by tire manufacturers and tire dealers/distributors, 49 CFR 574, ET SEQ. Tire manufacturers are required to provide tire registration forms to its tire dealers/distributors. Tire dealers/distributors who sell directly to consumers are required to provide tire registration forms to consumers at the time of sale. Tire dealers/distributors are also required to supply tire registration forms to other dealers for resale (or “resellers”).

When completing and mailing the tire registration forms, it is very important that you list all the information completely and accurately for the reasons stated above. Please fill out the shaded areas of the tire registration form (see example below) and include the name of the dealer/distributor, address, quantity of tires sold, and the complete D.O.T. Tire Identification Number for the tire(s) sold. If you assist the consumer in completing and mailing the registration forms, list his or her full name, complete address section, apply sufficient postage and mail. You may also register you tires online by visiting our website at WWW.GENERALTIRE.COM and clicking on the “Tire Registration” link.

If you do not complete and mail the registration form for the customer, please fill out the shaded areas of the tire registration form (see example below) and include the name of the dealer/distributor, address, quantity of tires sold, and the complete D.O.T. Tire Identification Number for the tire(s) sold. Then the customer enters his or her name and address on the form, apply postage and mail the form.

Penalties

Failure to comply with these requirements may result in civil penalties of \$5,000 for each violation and up to a maximum of \$15,000,000.

You may contact our Customer Relations Department at 1-800-847-3349 (in the US) or 1-855-453-1962 (in Canada). If you have questions about tire registration.

Remember, complete your obligations under the law.

IMPORTANT!

In case of a recall, we can reach you only if we have your name and address. You **MUST** send in this card to be on our recall list.

DO IT TODAY! Date of Sale ____/____/____

CUSTOMER'S NAME (Please print)

CUSTOMER'S ADDRESS

CITY STATE/PROVINCE ZIP/POSTAL CODE

OMB Approved OMB No. 2127-0050
Shaded Areas Must Be Filled In By Seller

Register **ONLY** tire brand checked ✓ below

Continental Tire

General Tire

SELLER COMPLETE

TIRE IDENTIFICATION NUMBERS												
QTY.	1	2	3	4	5	6	7	8	9	10	11	12

SELLER COMPLETE (Can be Rubber Stamped)

SELLER'S NAME

SELLER'S ADDRESS

CITY STATE/PROVINCE ZIP/POSTAL CODE

Federal law restricts above information provided to be used for tire recall purposes only!

GENERAL TIRE  TM

DELIVERS



GENERAL TIRE

DELIVERS

WWW.GENERALTIRE.COM